



AL2624-1805

Trusted for over 40 years by the US Military, Single Lid Cases offer 20% more protective material in the edges and corners, where it is needed most, ensuring that valuable equipment is kept safe from any unforeseen elements. Available in several sizes, these cases are completely customizable with a wide range of bolt-on options like document holders, casters, humidity indicators and much more.


- Molded-in, tongue-in-groove gasketed parting lines for splash resistance and tight seals, even after impact
- Reinforced corners and edges for additional impact protection
- Molded-in ribs and corrugations for secure, non-slip stacking, columnar strength, and added protection
- Recessed hardware for extra protection
- Positive anti-shear locks, which prevent lid separation after impact, and reduce stress on hardware
- Patented molded-in metal inserts for catch and hinge attachment points, which provide strength and spread loads to the container
- One-piece construction, molded from lightweight, high-impact polyethylene




CONFIGURATIONS




AL2624-1805
Standard



AL2624-1805-RP
Empty



AL2624-1805RPC
No Foam, With Casters



AL2624-1805RPFC
With Foam, With Casters

DIMENSIONS


| | |
|-------------------------|--|
| Interior (L×W×D) | 26.06 x 24.00" x 22.87 (66.2 x 61 x 58.1 cm) |
| Exterior (L×W×D) | 29.06 x 27.00" x 26.62 (73.8 x 68.6 x 67.6 cm) |
| Lid Depth | 5.06" (12.9 cm) |
| Bottom Depth | 17.81" (45.2 cm) |
| Total Depth | 22.87" (58.1 cm) |
| Int Volume | 8.28 ft ³ (0.234 m ³) |

MATERIALS

| | |
|-------------------|--|
| Body | RotoMolded Polyethylene |
| Latch | Steel (Nickel-black Plated) |
| O-Ring | Silicone Sponge |
| Foam | No Foam, empty case standard Optional PE and PU, 1 and 2 lb. options filled and lined |
| Purge Body | Aluminum |
| PRV Valve | .5 PSI Standard, Light Lift .25 PSI |
| Handle | Heavy Duty Injection Molded Standard |

| | |
|--------------------------|---|
| Optional Handles | Stainless Steel Passivate and Stainless Steel Black |
| Hardware | Yellow Carbon Steel Standard |
| Optional Hardware | Black Carbon Steel, Stainless Steel Passivate and Stainless Steel Black |

COLOURS

 Gray - 133 Fed Std
26270

WEIGHT

| | |
|---------------------------|-----------------------|
| Weight | 38.50 lbs (17.5 kg) |
| Buoyancy | 716.13 lbs (324.8 kg) |
| Master Pack Weight | 40.50 lbs (18.4 kg) |

TEMPERATURE

| | |
|----------------------------|------------------|
| Minimum Temperature | -20°F (-28.9 °C) |
| Maximum Temperature | 140°F (60 °C) |

OTHER

| | |
|-----------------|-----|
| Military | yes |
|-----------------|-----|

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 09-13-25