

# 1430

# **Protector**

Top Loader Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

#### • Unique top loading design

- 3 level Pick N Pluck<sup>™</sup> with convoluted lid foam
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors
- Optional shoulder strap available



#### **CONFIGURATIONS**



1430 Standard



1434 With Padded Dividers & Lid Organizer



**1437**With Padded Office Divider Set & Lid Organizer



1430NF No Foam



1430WF With Foam

# **DIMENSIONS**

Interior (L×W×D) 13.56 x 5.76" x 11.70 (34.4 x 14.6 x 29.7 cm) Exterior (L×W×D) 16.40 x 8.71" x 13.15 (41.7 x 22.1 x 33.4 cm)

 Lid Depth
 2.00" (5.1 cm)

 Bottom Depth
 9.70" (24.6 cm)

 Total Depth
 11.7" (29.7 cm)

 Int Volume
 0.53 ft³ (0.015 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

### **MATERIALS**

**Body** Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

### **COLOURS**



# WEIGHT

 Weight With Foam
 6.50 lbs (2.9 kg)

 Weight Empty
 5.60 lbs (2.5 kg)

 Buoyancy
 59.00 lbs (26.8 kg)

 Master Pack Weight
 8.09 lbs (3.7 kg)

#### **TEMPERATURE**

**Minimum Temperature** -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

# **CERTIFICATIONS**

IP67

Def Stan 81-41

#### **OTHER**

Master Pack1NameplateyesMilitaryyes

#### **ACCESSORIES**



**1431** 5 pc. Replacement Foam Set



1432 Strap Kit



**1433** Replacement O-ring



**1436** Office Divider Kit



**1430PF**Special Application Panel Frame



**1506TSA** TSA Lock



**1500D** Desiccant Silica Gel

Document created on 09-02-25