



# 1510

## Protector

Carry-On Case

The original case introduced over 45 years ago has since evolved into the global standard for equipment protection. The Protector Case series is designed to survive and trusted to travel to the harshest environments on earth.

The Pelican 1510 Protector Case provides military-grade protection for a wide variety of gear, from camera equipment to camping kits. It is available with foam, without foam, padded dividers, or TrekPak dividers. The Pelican 1510 Protector Case is the maximum airline carry-on size, so you can travel with your sensitive gear close at hand.

(Check with your airline for exact measurement requirements)

- Personalized nameplate service available
- Maximum airline carry on size\*
- **Strong polyurethane wheels with stainless steel bearings**
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded top and side handles
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors
- \* Check with your airline for exact measurement requirements.



## CONFIGURATIONS



## DIMENSIONS

|                              |                                               |
|------------------------------|-----------------------------------------------|
| <b>Interior (L×W×D)</b>      | 19.75 x 11.00" x 7.60 (50.2 x 27.9 x 19.3 cm) |
| <b>Exterior (L×W×D)</b>      | 22.00 x 13.81" x 9.00 (55.9 x 35.1 x 22.9 cm) |
| <b>Lid Depth</b>             | 1.79" (4.5 cm)                                |
| <b>Bottom Depth</b>          | 5.79" (14.7 cm)                               |
| <b>Total Depth</b>           | 7.58" (19.3 cm)                               |
| <b>Int Volume</b>            | 0.96 ft <sup>3</sup> (0.027 m <sup>3</sup> )  |
| <b>Padlock Hole Diameter</b> | 0.31" (0.8 cm)                                |

## MATERIALS

|               |                     |
|---------------|---------------------|
| <b>Body</b>   | Polypropylene       |
| <b>Latch</b>  | ABS                 |
| <b>O-Ring</b> | Polymer             |
| <b>Pins</b>   | Stainless Steel     |
| <b>Foam</b>   | 1.3 lb Polyurethane |

|                   |                                |
|-------------------|--------------------------------|
| <b>Purge Body</b> | ABS                            |
| <b>Purge Vent</b> | 3 Micron Hydrophobic Non-Woven |

COLOURS

|                                                                                         |                                                                                              |                                                                                            |
|-----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|
|  Black |  Desert Tan |  OD Green |
|-----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|

WEIGHT

|                                          |                     |
|------------------------------------------|---------------------|
| <b>Weight With Foam</b>                  | 13.60 lbs (6.2 kg)  |
| <b>Weight Empty</b>                      | 11.99 lbs (5.4 kg)  |
| <b>Buoyancy</b>                          | 64.15 lbs (29.1 kg) |
| <b>Weight With TrekPak / Foam Hybrid</b> | 14.94 lbs (6.8 kg)  |
| <b>Master Pack Weight</b>                | 32.43 lbs (14.7 kg) |

TEMPERATURE

|                            |                 |
|----------------------------|-----------------|
| <b>Minimum Temperature</b> | -40°F (-40 °C)  |
| <b>Maximum Temperature</b> | 190°F (87.8 °C) |

CERTIFICATIONS

|                       |
|-----------------------|
| <b>IP67</b>           |
| <b>Def Stan 81-41</b> |

OTHER

|                          |     |
|--------------------------|-----|
| <b>Wheels</b>            | 2   |
| <b>Extendable Handle</b> | yes |
| <b>Master Pack</b>       | 2   |
| <b>Nameplate</b>         | yes |
| <b>Reduced Area</b>      | yes |
| <b>Military</b>          | yes |

ACCESSORIES

|                                                                                     |                                                                                     |                                                                                     |                                                                                      |                                                                                       |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|  |  |  |  |  |
| <b>1511</b><br>4 pc. Replacement Foam Set                                           | <b>1513</b><br>Replacement O-ring                                                   | <b>1515</b><br>Padded Divider Set                                                   | <b>1519</b><br>Lid Organizer                                                         | <b>1510TPKIT</b><br>TrekPak Case Divider Kit                                          |
|  |  |  |  |                                                                                       |
| <b>1507</b><br>Quick Mounts - set of 4                                              | <b>1506TSA</b><br>TSA Lock                                                          | <b>1500D</b><br>Desiccant Silica Gel                                                | <b>1510MP</b><br>EZ-Click™ MOLLE Panel                                               |                                                                                       |

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 10-23-25*