

1610

Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Strong polyurethane wheels with stainless steel bearings
- · Watertight, crushproof, and dustproof
- 3 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve balances interior pressure, keeps water out
- · Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



1610 Standard



With Padded Dividers



1610NF No Foam



1610TPWith TrekPak Divider System



1610WF With Foam

DIMENSIONS

Interior (L×W×D) 21.78 x 16.69" x 10.62 (55.3 x 42.4 x 27 cm) Exterior (L×W×D) 24.83 x 19.69" x 11.88 (63.1 x 50 x 30.2 cm)

 Lid Depth
 2.05" (5.2 cm)

 Bottom Depth
 8.57" (21.8 cm)

 Total Depth
 10.62" (27 cm)

 Int Volume
 2.23 ft³ (0.063 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

MATERIALS

Body Polypropylene

Latch ABS
O-Ring Polymer
Pins Stainless Steel
Foam 1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLOURS

Black Desert Tan

WEIGHT

 Weight With Foam
 22.30 lbs (10.1 kg)

 Weight Empty
 19.50 lbs (8.8 kg)

 Buoyancy
 119.93 lbs (54.4 kg)

 Master Pack Weight
 25.55 lbs (11.6 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C)
Maximum Temperature 190°F (87.8 °C)

CERTIFICATIONS

IP67

Def Stan 81-41

OTHER

Wheels 2
Extendable Handle yes
Master Pack 1
Nameplate yes
Military yes

ACCESSORIES



Document created on 10-16-25