



1930

L1™

With a long lamp life and extended battery burn time, you won't be left in the dark with the L1™ flashlight. The polycarbonate body is resistant to chemicals, water and corrosion. The convenient tail switch for constant on/momentary is easy to operate. The L1™ is perfect for close quarter use. Packaged with 4 LR 44 1.5V alkaline coin cells, a break-a-way safety lanyard, and colored lens discs to preserve night vision. This handy flashlight offers a lot for its size.


- Built Pelican tough
- Super bright LED beam
- Unconditional Lifetime Guarantee of Excellence
- Security Lanyard



CONFIGURATIONS



1930
Standard



1930M
Merchandiser Display

DIMENSIONS

| | |
|---------------|----------------|
| Length | 2.64" (6.7 cm) |
|---------------|----------------|

MATERIALS

| | |
|--------------------------------|--------------------|
| Body | Polycarbonate (PC) |
| O-Ring | Ethylene Propylene |
| Lens | Polycarbonate (PC) |
| Shroud | Xenoy |
| Contact Spring Retainer | Phosphore Bronze |

COLOURS

| | |
|---|--|
|  Black |  High Visibility Yellow |
|---|--|

LIGHT SPECS

| | |
|------------------|-----|
| Lamp Type | LED |
|------------------|-----|

POWER

| | |
|---------------------|-------|
| Battery Size | LR 44 |
|---------------------|-------|

| | |
|---------------------------|----------|
| Battery Type | Alkaline |
| Battery Quantity | 4 |
| Batteries Included | yes |
| Volts | 6.0v |

WEIGHT

| | |
|---------------------------------|----------------|
| Weight With Batteries | 0.9 oz (26 gr) |
| Weight Without Batteries | 0.6 oz (17 gr) |
| Packaged Weight | 0.8 oz (23 gr) |

SWITCH






| | |
|--------------------|------------------|
| Switch Type | Push Button Tail |
| Light Modes | On / Off |

CERTIFICATIONS

| |
|----------------------------|
| Class I, Division 1 |
|----------------------------|

OTHER

| | |
|---------------------|-----|
| Minimum Pack | 12 |
| Military | yes |
| Package Code | C |

| FL1 STANDARD | HIGH |
|---|--------------|
|  | 12 LUMENS |
|  | 4h 15mins |
|  | 17m |
|  | 70cd |
|  | IPX4 |

ACCESSORIES

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 08-30-25