

IS3721-1103

ISP Case

Shifting loose cargo can slow down your ops and threaten the mission with damaged freight. The new ISP Case from Pelican™ virtually eliminates load movement with a unique Inter-Stacking Pattern (ISP). The patent pending system is compatible across 6 different case sizes from 4 to 25 cubic feet of storage. Equipped with a silicone sponge O-ring and pressure release valves, the ISP Case is impervious to extreme weather and wet conditions.

The system is designed to maximize the volume of standard logistics platforms. Whether loading standard pallets, NATO pallets, JMIC containers, 463L pallets or sea containers, the ISP Case system will make the most efficient use of cargo space.

With its Inter-Stacking Pattern there is no question where the next case belongs. The disc pattern bottom mates with the wave pattern on the case below, literally falling and locking into place. Cross-stacking builds incredibly tight loads that can save time with strapping or netting.

- Standard Features:
 - Removable Lid
 - Freebreathing
 - Black Carbon Steel, All Catch and Strike Hardware
 - 8 Large Injection Molded Comfort Grip handles
 - Colors: BLACK_032, GREY_133, OLIVE DRAB_137, RED_130, TAN_250
 - Molded-In Edge Casters
- Inter-Stacking Pattern Cases for NATO pallets, JMIC containers, 463L pallets or sea containers
- Configurable Features:
 - Hardware: Black Stainless Steel
 - Pressure Relief Valve (PRV) with Closed Gasket
 - Hinged Lid
 - Metal Handles: Black Carbon Steel, Stainless Steel Passivate or

Stainless Steel Black

- 2 Cable Catch locks per case
- 2 Padlock Hasps per case
- 3" X 5" Horizontal Card Holder
- Front Labels, STD Labels and ATA Labels
- Pressure Relief Valve
- Humidity Indicator
- Lift Grip (750 lbs LC each installed)



CONFIGURATIONS



IS3721-1103 Standard



IS3721-1103-No-Foam No Foam

Interior (L×W×D) 37.00 x 21.00" x 14.00 (94 x 53.3 x 35.6 cm) Exterior (L×W×D) 40.00 x 24.00" x 16.00 (101.6 x 61 x 40.6 cm)

 Lid Depth
 3.00" (7.6 cm)

 Bottom Depth
 11.00" (27.9 cm)

 Total Depth
 14" (35.6 cm)

 Int Volume
 6.3 ft³ (0.178 m³)

MATERIALS

BodyRotoMolded PolyethyleneLatchSteel (Nickel-black Plated)

O-Ring Silicone Sponge
Pins Stainless Steel
Pins (Alt) Aluminum
Purge Body Aluminum

COLOURS

Black - 032 Fed Std

27040

Olive Drab - 137 Fed Std 34096

Gray - 133 Fed Std 26270

Tan - 250 Fed Std

20372

Red - 130 Fed Std 21105

WEIGHT

 Weight With Foam
 52.00 lbs (23.6 kg)

 Weight Empty
 38.00 lbs (17.2 kg)

TEMPERATURE

 $\begin{tabular}{ll} \begin{tabular}{ll} \beg$

CERTIFICATIONS

MIL-STD-810F

OTHER

Wheels 2 Max Drag Weight 150.00

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 10-18-25