

1600EMS

Protector

EMS Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican $^{\text{\tiny TM}}$ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- 1600 Case customized for EMS personnel
- CONTENTS NOT INCLUDED
- Watertight, crushproof, and dustproof
- Automatic pressure equalization valve balances interior pressure, keeps water out
- \bullet Lid organizer clear cover with VELCRO $\mbox{\ensuremath{\$}}$ brand fasteners keep supplies in place during transport
- Lifetime Guarantee of Excellence
- Multi layer lid organizer with numerous clean pockets find everything right away
- Padded dividers with adjustable walls for customizing compartments to any size.
- Stainless steel padlock protectors



DIMENSIONS

Interior (L×W×D) 21.51 x 16.54" x 7.99 (54.6 x 42 x 20.3 cm) Exterior (L×W×D) 24.39 x 19.36" x 8.79 (62 x 49.2 x 22.3 cm)

 Lid Depth
 1.75" (4.4 cm)

 Bottom Depth
 6.12" (15.5 cm)

 Total Depth
 7.87" (20 cm)

 Int Volume
 1.65 ft³ (0.047 m³)

 Padlock Hole Diameter
 5/16" (12.7 cm)

MATERIALS

Body Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLOURS

Black Orange

WEIGHT

 Weight With Foam
 18.00 lbs (8.2 kg)

 Buoyancy
 74.96 lbs (34 kg)

 Master Pack Weight
 18.50 lbs (8.4 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

CERTIFICATIONS

IP67 MIL C-4150J Def Stan 81-41 ATA 300

OTHER

Master Pack1Nameplateyes

ACCESSORIES



1605EMSEMS Accessory Set (Lid Organizer and Divider Set)



1506TSA TSA Lock



1500D Desiccant Silica Gel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 10-17-25