



iM2750

Storm

Travel Case

The Pelican™ Storm Case™ has the same legendary DNA as our Pelican Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch.

Guaranteed for life, the Pelican Storm case is made in the USA and engineered using the finest components.

- Four Press & Pull Latches
- Guaranteed For Life
- Two Padlockable Hasps
- Two Double-layered, Soft-grip Handles
- Powerful Hinges
- O-ring seal



CONFIGURATIONS



iM2750
Standard



iM2750-X0000
No Foam



iM2750-X0002
With Padded Dividers



iM2750-X0001
With Foam

DIMENSIONS

Interior (LxWxD)	22.00 x 17.00" x 12.70 (55.9 x 43.2 x 32.3 cm)
Exterior (LxWxD)	24.60 x 19.70" x 14.40 (62.5 x 50 x 36.6 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	10.70" (27.2 cm)
Total Depth	12.7" (32.3 cm)
Int Volume	2.75 ft ³ (0.078 m ³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Injection Molded HPX™ high performance resin
Latch	Valox - Polybutylene Terephthalate (PBT)
Latch (Alt)	Xenoy - Polyester/Polycarbonate blend
O-Ring	EPDM
Pins	Stainless Steel
Pins (Alt)	Aluminum
Foam	1.3/1.35 polyester
Purge Body	Valox - Polybutylene Terephthalate (PBT)
Purge Body (Alt)	Xenoy - Polyester/Polycarbonate blend
Purge Vent	Gortex membrane

COLOURS

■ Black

■ OD Green

■ Yellow

WEIGHT

Weight With Foam	23.40 lbs (10.6 kg)
Weight Empty	18.50 lbs (8.4 kg)
Buoyancy	173.40 lbs (78.7 kg)
Master Pack Weight	25.20 lbs (11.4 kg)

TEMPERATURE

Minimum Temperature	-20°F (-28.9 °C)
Maximum Temperature	140°F (60 °C)

CERTIFICATIONS

IP67

OTHER

Extendable Handle	yes
Master Pack	1
Military	yes


ACCESSORIES



iM27XX-UTILITYORG
Utility Organizer



iM2750-BEZEL-LID
Lid Bezel Kit



iM2750-BEZEL
Base Bezel Kit



iM2750-FOAM
7 pc. Replacement Foam Set



iM-LIDSTAY
Lid Stay



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



1500CI
Corrosion Intercept Kit

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 07-24-24