

1506 _{Air}

Pelican understands that finding the right protection, with the perfect fit for your gear, is a priority. Pelican[™] Air began with long protection and quickly grew to offer you deep protection. The time has come to combine those two in order to create Pelican's new Long/Deep Series. Gone are the days of dangerously forcing your equipment into the wrong size case or leaving it unprotected with no other options. With Pelican's Long/Deep series, we've created the missing link so that no matter the demands of your gear, Pelican has you covered.

• Automatic pressure equalization valve - balances interior pressure, keeps water out

- Fold down over-molded handle
- Stainless steel padlock protectors

• Super-light proprietary HPX Polymer makes this case up to 40% lighter than the competition

- Limited Lifetime Warranty
- Super-light proprietary HPX²[™] Polymer up to 40% lighter
- Waterproof O-ring seal
- User-customizable Pick N Pluck[™] foam
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified
- Made in the USA

CONFIGURATIONS



1506 Standard



1506WF With Foam



1506NF No Foam



1506TP With TrekPak Divider System

DIMENSIONS

Interior (L×W×D)	18.70 x 9.40" x 7.80 (47.5 x 23.9 x 19.8 cm)
Exterior (L×W×D)	20.12 x 12.02" x 8.56 (51.1 x 30.5 x 21.7 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	5.80" (14.7 cm)
Total Depth	7.8" (19.8 cm)
Int Volume	0.79 ft ³ (0.022 m ³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

BodyProprietary Polypropylene BlendLatchABSO-RingEPDMPurge BodyABS

Purge Vent

COLOURS

Black


WEIGHT

Weight With Foam	6.30 lbs (2.9 kg)
Weight Empty	5.35 lbs (2.4 kg)
Buoyancy	51.69 lbs (23.4 kg)

TEMPERATURE

Minimum Temperature	-60°F (-51.1 °C)
Maximum Temperature	160°F (71.1 °C)

ACCESSORIES



1506AirFS 4 pc. Replacement Foam Set



 Pelican

 23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

 sales@pelican.com
 • www.pelican.com

Document created on 04-26-24