



1460TOOL

Protector

Mobile Tool Chest

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Also available without tray dividers
- Personalized nameplate service available
- **Adjustable and removable tray dividers for easy customization**
- **Top lid opens up to 180° for on-the-field anti-roll stability when open**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handles
- Easy open double-throw latches
- Lifetime Guarantee of Excellence (Tray system not covered by lifetime warranty)
- O-ring seal for dust and water resistant seal (IP66)
- Open cell core with solid wall design - strong, light weight
- Tray sizes: Top tray 17.65" x 8.2" x 2.4" (44.83 x 20.83 x 6.10 cm) and bottom tray 17.3" x 8.0" x 2.3" (43.94 x 20.32 x 5.84 cm)



DIMENSIONS

Interior (LxWxD)	18.54 x 9.92" x 10.92 (47.1 x 25.2 x 27.7 cm)
Exterior (LxWxD)	20.85 x 12.73" x 12.75 (53 x 32.3 x 32.4 cm)
Lid Depth	4.91" (12.5 cm)
Bottom Depth	6.01" (15.3 cm)
Total Depth	10.92" (27.7 cm)
Int Volume	1.16 ft ³ (0.033 m ³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Polypropylene
Latch	EXL
O-Ring	Polymer
Pins	Stainless Steel
Foam	Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

■ Black

WEIGHT

Weight With Foam	13.00 lbs (5.9 kg)
Buoyancy	82.00 lbs (37.2 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C)
Maximum Temperature 210°F (98.9 °C)

CERTIFICATIONS

IP66

OTHER

Nameplate yes
Military yes

ACCESSORIES



1463
Replacement O-ring



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



1500CI
Corrosion Intercept Kit

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 10-14-24