



1495CC1

Protector

Laptop Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Combination Lock Information
- **3 dial combination lock included**
- **Fits up to 17" laptops**
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down over-molded handle
- Lid organizer, shock absorbing tray, and padded shoulder strap
- Nylon padded computer sleeve and accessories pouch
- Stainless steel padlock protectors



DIMENSIONS

Interior (LxWxD)	18.87 x 13.12" x 3.81 (47.9 x 33.3 x 9.7 cm)
Exterior (LxWxD)	21.62 x 17.25" x 4.87 (54.9 x 43.8 x 12.4 cm)
Lid Depth	1.12" (2.8 cm)
Bottom Depth	2.68" (6.8 cm)
Total Depth	3.8" (9.7 cm)
Int Volume	0.55 ft³ (0.016 m³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

■ Black

WEIGHT

Weight With Foam	11.10 lbs (5 kg)
Buoyancy	45.15 lbs (20.5 kg)
Master Pack Weight	28.00 lbs (12.7 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

CERTIFICATIONS

IP67	
Def Stan 81-41	

OTHER

Master Pack	2
Nameplate	yes

ACCESSORIES

				
1483 Replacement O-ring	1495ALI Attache/Computer Lid Insert	1495CBI Computer Bottom Insert	1495HDF 4 lb. High Density Foam	1506TSA TSA Lock
				
1500D Desiccant Silica Gel	1500CI Corrosion Intercept Kit			

Pelican
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 04-16-24