



# 1555

## Air

Pelican™ Air cases are the first in a series of remarkable innovations engineered by Pelican, the pioneers of protective cases. For over 40 years Pelican has designed and crafted the most influential protective cases in the world, and we're just getting started. With the launch of the Pelican™ Air line of cases, we're redefining the future of protection with a remarkable union of light and tough.

- Automatic Purge Valve - Keeps water and dust out while balancing air pressure
- Super-light proprietary HPX<sup>2</sup>™ Polymer
- Business card holder



## CONFIGURATIONS



**1555**  
Standard



**1555NF**  
No Foam



**1555WD**  
With Padded Dividers



**1555TP**  
With TrekPak Divider System



**1555WF**  
With Foam

## DIMENSIONS

<b>Interior (LxWxD)</b>	23.00 x 12.75" x 7.50 (58.4 x 32.4 x 19.1 cm)
<b>Exterior (LxWxD)</b>	24.76 x 15.46" x 8.24 (62.9 x 39.3 x 20.9 cm)
<b>Lid Depth</b>	2.00" (5.1 cm)
<b>Bottom Depth</b>	5.50" (14 cm)
<b>Total Depth</b>	7.5" (19.1 cm)
<b>Int Volume</b>	1.27 ft <sup>3</sup> (0.036 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	5/16" (8 mm)

## MATERIALS

<b>Body</b>	Proprietary Polypropylene Blend
<b>Latch</b>	ABS
<b>O-Ring</b>	EPDM
<b>Purge Body</b>	ABS
<b>Purge Vent</b>	Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

## COLOURS

 Black	 Orange	 Silver	 Yellow
---	--	--	--

## WEIGHT

<b>Weight With Foam</b>	9.02 lbs (4.1 kg)
<b>Weight Empty</b>	7.37 lbs (3.3 kg)

**Buoyancy**

81.20 lbs (36.8 kg)

## TEMPERATURE

---

**Minimum Temperature** -60°F (-51.1 °C)

**Maximum Temperature** 160°F (71.1 °C)

## ACCESSORIES

---



**1555AirFS**  
4 pc. Replacement Foam Set



**1555AirDS**  
Padded Divider Set



**1555TPKIT**  
TrekPak Case Divider Kit



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel



**PL2**  
Padlock (2 pack)

---

### Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 10-15-21*