



3315R

Ultra compact, special designed lithium rechargeable and safety certified make the Pelican™ 3315R one of the most versatile work lights available today. Its compact design fits comfortably in your hand and requires little space for storage or transport. The 3315R produces up to 132 lumens and provides up to 34 hours of continuous run time. 3 modes are provided, High / Low / Flashing. There is a full time battery level indicator built into the power switch so you'll always know when it's time to recharge. Additionally, there is a right angle adapter accessory (sold separately) that provides hands free lighting. The right angle adapter also allows the light head to articulate, directing the light exactly where you need it.

- IPX7 Waterproof
- Full Time Battery Level Indication
- 3 modes High / Strobe / Low
- Safety Certified Class I, Division 1 / IECEx ia
- Lanyard (included)
- Articulating right angle adapter with clip (sold separately)
- Special Lithium rechargeable battery provides 2,000 cycles (a 300% increase)
- Up to 132 Lumens
- Up to 34 hours, 15 minutes run time




DIMENSIONS

| | |
|---------------|-----------------|
| Length | 6.11" (15.5 cm) |
|---------------|-----------------|

MATERIALS

| | |
|---------------|---------------------------------------|
| Body | Anti-static Impact Modified PC/PBT |
| O-Ring | EPDM |
| Lens | Anti-static coated Polycarbonate (PC) |
| Shroud | Anti-static Impact Modified PC/PBT |

COLOURS

| | |
|---|------------------------|
|  | High Visibility Yellow |
|---|------------------------|

LIGHT SPECS

| | |
|------------------|-----|
| Lamp Type | LED |
|------------------|-----|

POWER

| | |
|--------------------------------|------------------------|
| Battery Size | 18650 |
| Battery Type | Lithium Iron Phosphate |
| Battery Quantity | 1 |
| Batteries Included | yes |
| Rechargeable | yes |
| Charge Time | 10 hrs |
| Battery Level Indicator | RGB LED |
| Volts | 3.2v |

WEIGHT

| | |
|--------------------------|-----------------|
| Weight With Batteries | 4.6 oz (130 gr) |
| Weight Without Batteries | 3.0 oz (85 gr) |

SWITCH






| | |
|-------------|-----------------------|
| Switch Type | Push Button |
| Light Modes | High / Low / Flashing |

CERTIFICATIONS

| |
|---------------------|
| Class I, Division 1 |
| IECEX ia |
| InMetro |

OTHER

| | |
|--------------|---|
| Minimum Pack | 1 |
| Package Code | C |

| FL1 STANDARD | HIGH | LOW |
|---|---------------|--------------|
|  | 132 LUMENS | 15 LUMENS |
|  | 5h 0mins | 34h 0mins |
|  | 108m | 35m |
|  | 2931cd | 308cd |
|  | IP67 | |

ACCESSORIES



3317
Right Angle Adapter



8056F
12v Plug-in for Fast Charger



3318
Deck/Dash Charger Base Unit



2467F
110V Transformer (USA)



6061F
Direct Wiring Rig for Fast Charger

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 04-19-24