



## 3765PL

Right Angle Light

- Compact and Lightweight
- NFPA Compliant (National Fire Protection Agency) 1901
- Also Operates on 4 Standard AA Alkaline Batteries




### DIMENSIONS

<b>Length</b>	5.36" (13.6 cm)
---------------	-----------------

### MATERIALS

<b>Body</b>	ABS
<b>O-Ring</b>	Buna-N
<b>Lens</b>	Polycarbonate (PC)
<b>Shroud</b>	Photo luminescent Polycarbonate (PC)
<b>Clip</b>	Xenoy

### COLOURS

 High Visibility Yellow

### LIGHT SPECS

<b>Lamp Type</b>	LED
<b>Lamp Secondary Type</b>	LED

### POWER

<b>Battery Size</b>	AA
<b>Battery Type</b>	NiMH
<b>Battery Quantity</b>	4
<b>Batteries Included</b>	yes
<b>Rechargeable</b>	yes
<b>Charge Time</b>	3 hrs 30 mins
<b>Battery Level Indicator</b>	3 Blue LEDs
<b>Volts</b>	4.8v

### WEIGHT

<b>Weight With Batteries</b>	14.6 oz (414 gr)
------------------------------	------------------

**Weight Without Batteries**

11.0 oz (312 gr)

**SWITCH**

**Switch Type**

Push Button

**Light Modes**

High / Low / Flashing

**CERTIFICATIONS**

**Class I, Division 1**

**Class I, Division 2**






**OTHER**

**Minimum Pack**

1

**Package Code**

B

<b>FL1 STANDARD</b>	<b>HIGH</b>	<b>LOW</b>	<b>DOWNCAST</b>	<b>FLASHING</b>
	237 LUMENS	113 LUMENS	32 LUMENS	140 LUMENS
	3h 0mins	6h 30mins	14h 0mins	9h 0mins
	301m	193m	28m	274m
	22720cd	9354cd	192cd	18784cd
	IPX4			

**ACCESSORIES**



**3769**  
Replacement Battery



**2467F**  
110V Transformer (USA)



**6061F**  
Direct Wiring Rig for Fast Charger



**8056F**  
12v Plug-in for Fast Charger

---

**Pelican**  
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 12-11-24*