



## 2755CC

Headlamp

When you can't see the difference between one color cable from another, the job may be compromised. Now you can trust our select flashlights with new Correct Color technology to stop the guess work.

Common LED lights can produce an intense beam and lower CRI (Color Rendering Index), making it difficult to distinguish between different color cables and overpower your work area with blinding bright light. Our new Correct Color flashlights are engineered with a higher CRI(90+ Color Rendering Index) allowing you to see color more accurately in your work environment. And with a low temperature beam (similar to incandescent flashlights ) you get the benefits of our Correct Color technology that doesn't outshine the details.

- 2 Modes: High / Low
- 3 AAA Alkaline Batteries
- Up to 50m Beam Distance
- Up to 72 Lumens
- Learn more about Correct Color Lights




### DIMENSIONS

<b>Length</b>	2.25" (5.7 cm)
---------------	----------------

### MATERIALS

<b>Body</b>	Polycarbonate (PC)
<b>O-Ring</b>	Over-molded TPR
<b>Lens</b>	Polycarbonate (PC)
<b>Shroud</b>	Polycarbonate (PC)

### COLOURS

 High Visibility Yellow

### LIGHT SPECS

<b>Lamp Type</b>	LED
------------------	-----

### POWER

<b>Battery Size</b>	AAA
<b>Battery Type</b>	Alkaline
<b>Battery Quantity</b>	3
<b>Batteries Included</b>	yes
<b>Battery Level Indicator</b>	Low battery warning
<b>Volts</b>	4.5v

### WEIGHT

<b>Weight With Batteries</b>	3.4 oz (96 gr)
<b>Weight Without Batteries</b>	2.1 oz (60 gr)

## SWITCH






<b>Switch Type</b>	Push Button
<b>Light Modes</b>	High / Low / Flashing

## CERTIFICATIONS

**Class I, Division 1**  
**IECEX ia**

## OTHER

**Minimum Pack** 1

FL1 STANDARD	HIGH	LOW
	72 LUMENS	36 LUMENS
	6h 45mins	15h 0mins
	50m	35m
	632cd	302cd
	IP54	

## ACCESSORIES



**2748**  
Strapless Headlamp Adapter

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 09-19-24*