AL2727-2704

Trusted for over 40 years by the US Military, Single Lid Cases offer 20% more protective material in the edges and corners, where it is needed most, ensuring that valuable equipment is kept safe from any unforeseen elements. Available in several sizes, these cases are completely customizable with a wide range of bolt-on options like document holders, casters, humidity indicators and much more.

• Lignes de partage résistantes aux éclaboussures avec joints à rainure et languette moulés étroitement serrés en permanence, même
• Angles et bords renforcés pour protection additionnelle contre les impacts
• Épaulements et cannelures moulées pour empilement súr et sans glissement, plus de force colonnaire et protection renforcée
• Matériel encastré pour une protection renforcée
• Verrous anti-tiraillement positif prévenant la séparation du couvercle après impact et réduisant les contraintes sur le matériel
• Inserts métalliques surmoulés brevetés aux points d'attache pour fermeture et charnière pour une meilleure résistance
• Construction monobloc, moulée à partir de polyéthylène léger résistant aux chocs

DIMENSIONS

INTÉRIEUR	27.00 x 27.00" x 30.84 (68.6 x 68.6 x 78.3 cm)
EXTÉRIEUR	30.00 x 30.00" x 33.03 (76.2 x 76.2 x 83.9 cm)
profondeur couvercle	3.87" (9.8 cm)
profondeur fond	26.97" (68.5 cm)
profondeur totale	30.84" (78.3 cm)
volume intérieur	13.01 ft^3 (0.368 m^3)

MATÉRIAUX

corps	RotoMolded Polyethylene
loquet	Steel (Nickel-black Plated)
joint torique	Silicone Sponge
mousse	No Foam, empty case standard Optional PE and PU, 1 and 2 lb. options filled and lined
corps de purge	Aluminum
PRV Valve	.5 PSI Standard, Light Lift .25 PSI
poignée	Heavy Duty Injection Molded Standard
Optional Handles	Stainless Steel Passivate and Stainless Steel Black
matériel	Yellow Carbon Steel Standard
Optional Hardware	Black Carbon Steel, Stainless Steel Passivate and Stainless Steel Black

COULEURS

Gray - 133 Fed Std 26270

POIDS

poids	47.60 lbs (21.6 kg)
flottabilité	1026.44 lbs (465.6 kg)
Master Pack Weight	49.60 lbs (22.5 kg)

TEMPÉRATURE

température minimale	-20°F (-28.9 °C)
température maximale	140°F (60 °C)

AUTRES

Domaine militaire	Oui

Pelican
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 04-26-24