



9415i

9410L + Safety = 9415i

Everything that's great about the 9410L LED Lantern, plus safety certificates

At just 1.4kg (3 pounds) and 392 lumens, the 9415i LED Lantern packs the power without the weight. Four LEDs, powered by the latest generation Ni-MH batteries illuminate a distance of 392 meters. And it's loaded with innovative technology and features you have come to expect from Pelican.

Safety certified for the most volatile work areas, the 9415i LED Lantern is safe and one of the most compact, high output lanterns on the market.

- Built Pelican tough
- Handy push button on/off switch
- High/Low/Flashing Modes
- Super bright LED beam
- Carrying Strap included



DIMENSIONS

Length	8.75" (22.2 cm)
--------	-----------------

MATERIALS

Body	Anti-static Impact Modified PC/PBT
O-Ring	EPDM
Lens	Anti-static coated Polycarbonate (PC)
Shroud	Anti-static Impact Modified PC/PBT

COLORS

 High Visibility Yellow
--

LIGHT SPECS

Lamp Type	LED
-----------	-----

POWER

Battery Size	C
Battery Type	NiMH
Battery Quantity	4
Batteries Included	yes
Rechargeable	yes
Charge Time	15 hrs
Battery Level Indicator	RGB LED
Volts	4.8v

WEIGHT

Weight With Batteries	58.2 oz (1650 gr)
Weight Without Batteries	0.0 oz (0 gr)

SWITCH

Switch Type	Push Button
Light Modes	High / Low / Flashing

CERTIFICATIONS

IECEX ia
ATEX Zone 0
InMetro

OTHER

Minimum Pack	1
Package Code	B

FL1 STANDARD	HIGH	LOW
	392 LUMENS	144 LUMENS
	4h 30mins	11h 0mins
	392m	234m
	32767cd	13747cd
	IPX4	

ACCESSORIES

				
9416 Deck/Dash Charger Base Unit	6057F 110V Transformer (USA)	6061F Direct Wiring Rig for Fast Charger	8056F 12v Plug-in for Fast Charger	941820 Replacement Battery

Pelican
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 08-18-25