

# 9415

#### 9410L + SAFETY = 9415

Everything that's great about the 9410L LED Lantern, plus safety certifications At just 3 pounds and 588\* lumens, the new 9415 LED Lantern packs the power without the weight. Four LEDs, powered by the latest generation Ni-MH batteries illuminate a distance of 314 yards (288\* meters). And it's loaded with innovative technology and features you have come to expect from Pelican. Whether you're on a USAR team or the 3rd shift at a refinery, you'll appreciate the compact size and high output of the new 9415 LED Lantern.

Safety approved for the most volatile work areas, the 9415 LED Lantern is safe and one of the most compact, high output lanterns on the market. 9415 LED Lantern: Lightweight, big LED performance you can trust. \*Performance data is to FL 1 standards

- · Built Pelican tough
- · Handy push button on/off switch
- High/Low/Flashing Modes
- Super bright LED beam
- Safety Certified Class I, Division I
- Approved to NFPA (National Fire Protection Association) 1901
- · Carrying Strap included



#### **DIMENSIONS**

**Length** 8.75" (22.2 cm)

#### **MATERIALS**

Body ABS O-Ring EPDM

**Lens** Polycarbonate (PC)

Shroud EXL

#### **COLORS**

High Visibility Yellow

#### LIGHT SPECS

Lamp Type LED

### **POWER**

Battery Type NiMH
Battery Quantity 4
Batteries Included yes
Rechargeable yes
Charge Time 15 hrs
Battery Level Indicator RGB LED
Volts 4.8v

## WEIGHT

Weight With Batteries Weight Without

49.3 oz (1398 gr)

Weight Witho Batteries 0.0 oz (0 gr)

## **SWITCH**

Switch Type Light Modes Push Button

High / Low / Flashing

## **CERTIFICATIONS**

Class I, Division 1

## OTHER

Minimum Pack Package Code 1 B

| FL1 STANDARD | HIGH          |  |
|--------------|---------------|--|
| 314          | 588<br>LUMENS |  |

| 314 | 588<br>LUMENS | 224<br>LUMENS |
|-----|---------------|---------------|
|     | 4h 30mins     | 11h 30mins    |
|     | 288m          | 176m          |
|     | 20792cd       | 7787cd        |
|     | IPX4          |               |

LOW

## **ACCESSORIES**







**6057F** 110V Transformer (USA)



**6061F**Direct Wiring Rig for Fast
Charger



**8056F** 12v Plug-in for Fast Charger



**9418**Replacement Battery

#### Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com

Document created on 08-31-25