

1700

Protector

Long Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican $^{\text{m}}$ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Strong polyurethane wheels with stainless steel bearings
- Watertight, crushproof, and dustproof
- 3-piece foam set
- Automatic pressure equalization valve balances interior pressure, keeps water out
- · Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors
- 12 lid bosses for mounting of multiple 1500MP EZ-Click™ MOLLE Panels
- Hi-density foam tray option for 10 firearms
- Fold-down side handles on both ends additional carrying options
- New fold-down over-molded top and side handles



CONFIGURATIONS



DIMENSIONS

Interior (L×W×D) 35.76 x 13.73" x 5.35 (90.8 x 34.9 x 13.6 cm) Exterior (L×W×D) 38.47 x 16.42" x 6.14 (97.7 x 41.7 x 15.6 cm)

 Int Volume
 1.52 ft³ (0.043 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

MATERIALS

Body Polypropylene

Latch ABS
O-Ring Polymer
Pins Stainless Steel
Foam 1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLORS

Black

Desert Tan

OD Green

WEIGHT

Weight With Foam 16.85 lbs (7.6 kg)
Weight Empty 15.10 lbs (6.8 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

OTHER

Military

yes

ACCESSORIES



1500MP EZ-Click™ MOLLE Panel



1506TSA TSA Lock



1500D Desiccant Silica Gel




1703 Replacement O-ring



LGMT-001PProtector Case Roof Mount



1701FS 3 pc. Replacement Foam Set



1700PRS RE-SET Kit

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 09-02-25