

# 1430 Protector

Top Loader Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican<sup>™</sup> Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

## • Unique top loading design

- 3 level Pick N Pluck<sup>™</sup> with convoluted lid foam
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors
- Optional shoulder strap available



# CONFIGURATIONS



1430

Standard

**1434** With Padded Dividers & Lid Organizer



1437 With Padded Office Divider Set & Lid Organizer



**1430NF** No Foam



**1430WF** With Foam

# DIMENSIONS

Interior (L×W×D)	13.56 x 5.76" x 11.70 (34.4 x 14.6 x 29.7 cm)
Exterior (L×W×D)	16.40 x 8.71" x 13.15 (41.7 x 22.1 x 33.4 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	9.70" (24.6 cm)
Total Depth	11.7" (29.7 cm)
Int Volume	0.53 ft <sup>3</sup> (0.015 m <sup>3</sup> )
Padlock Hole Diameter	0.31" (0.8 cm)

#### MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS

#### Purge Vent

## COLORS

Black

## WEIGHT

Weight With Foam	6.50 lbs (2.9 kg)
Weight Empty	5.60 lbs (2.5 kg)
Buoyancy	59.00 lbs (26.8 kg)
Master Pack Weight	8.09 lbs (3.7 kg)

## TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	190°F (87.8 °C)

## CERTIFICATIONS

IP67	
Def Stan	81-41

### OTHER

Nameplate yes	
Military yes	

## ACCESSORIES



 Pelican

 23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

 sales@pelican.com
 • www.pelican.com

Document created on 09-13-25