

# 1495

## **Protector**

Laptop Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Combination Lock Information
- 3 dial combination lock included
- Fits up to 17" laptops
- · Watertight, crushproof, and dustproof
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down over-molded handle
- Lifetime Guarantee of Excellence
- Padded shoulder strap
- Pick N Pluck<sup>™</sup> with convoluted lid foam
- Stainless steel padlock protectors



#### **CONFIGURATIONS**



**1495** Standard



**1495NF** No Foam



1495WF With Foam

#### **DIMENSIONS**

Interior (L×W×D) 18.87 x 13.12" x 3.81 (47.9 x 33.3 x 9.7 cm) Exterior (L×W×D) 21.62 x 17.25" x 4.87 (54.9 x 43.8 x 12.4 cm)

 Lid Depth
 1.12" (2.8 cm)

 Bottom Depth
 2.68" (6.8 cm)

 Total Depth
 3.8" (9.7 cm)

 Int Volume
 0.55 ft³ (0.016 m³)

 Padlock Hole Diameter
 0.25" (0.6 cm)

#### **MATERIALS**

**Body** Polypropylene

LatchABSO-RingPolymerPinsStainless Steel

**Foam** 1.3 lb Polyurethane

**Purge Body** 

**Purge Vent** 3 Micron Hydrophobic Non-Woven

### **COLORS**

Black Desert Tan

#### WEIGHT

Weight With Foam 8.37 lbs (3.8 kg) **Weight Empty** 7.23 lbs (3.3 kg) **Buoyancy** 45.15 lbs (20.5 kg) **Master Pack Weight** 23.00 lbs (10.4 kg)

### **TEMPERATURE**

**Minimum Temperature** -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

#### **CERTIFICATIONS**

IP67

Def Stan 81-41

#### **OTHER**

**Master Pack** 2 Nameplate yes

### **ACCESSORIES**



1472

Shoulder Strap



1481 3 pc. Replacement Foam Set



1483 Replacement O-ring



1507 Quick Mounts - set of 4



1506TSA



1500D Desiccant Silica Gel

Document created on 11-02-25