



1510

Protector

Carry-On Case

The original case introduced over 45 years ago has since evolved into the global standard for equipment protection. The Protector Case series is designed to survive and trusted to travel to the harshest environments on earth.

The Pelican 1510 Protector Case provides military-grade protection for a wide variety of gear, from camera equipment to camping kits. It is available with foam, without foam, padded dividers, or TrekPak dividers. The Pelican 1510 Protector Case is the maximum airline carry-on size, so you can travel with your sensitive gear close at hand.

(Check with your airline for exact measurement requirements)

- Personalized nameplate service available
- Maximum airline carry on size*
- **Strong polyurethane wheels with stainless steel bearings**
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded top and side handles
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors
- * Check with your airline for exact measurement requirements.



CONFIGURATIONS



DIMENSIONS

Interior (L×W×D)	19.75 x 11.00" x 7.60 (50.2 x 27.9 x 19.3 cm)
Exterior (L×W×D)	22.00 x 13.81" x 9.00 (55.9 x 35.1 x 22.9 cm)
Lid Depth	1.79" (4.5 cm)
Bottom Depth	5.79" (14.7 cm)
Total Depth	7.58" (19.3 cm)
Int Volume	0.96 ft ³ (0.027 m ³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane

Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLORS

 Black	 Desert Tan	 OD Green
---	--	--

WEIGHT

Weight With Foam	13.60 lbs (6.2 kg)
Weight Empty	11.99 lbs (5.4 kg)
Buoyancy	64.15 lbs (29.1 kg)
Weight With TrekPak / Foam Hybrid	14.94 lbs (6.8 kg)
Master Pack Weight	32.43 lbs (14.7 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	190°F (87.8 °C)

CERTIFICATIONS

IP67
Def Stan 81-41

OTHER

Wheels	2
Extendable Handle	yes
Master Pack	2
Nameplate	yes
Reduced Area	yes
Military	yes

ACCESSORIES

				
1511 4 pc. Replacement Foam Set	1513 Replacement O-ring	1515 Padded Divider Set	1519 Lid Organizer	1510TPKIT TrekPak Case Divider Kit
				
1510TPDIV Extra TrekPak Dividers	1507 Quick Mounts - set of 4	1506TSA TSA Lock	1500D Desiccant Silica Gel	1510MP EZ-Click™ MOLLE Panel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 08-23-25