

1620

Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Strong polyurethane wheels with stainless steel bearings
- · Watertight, crushproof, and dustproof
- 4 level Pick N Pluck[™] with convoluted lid foam
- Automatic pressure equalization valve balances interior pressure, keeps water out
- · Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



1620 Standard



1624With Padded Dividers



1620NF No Foam



1620WF With Foam

DIMENSIONS

Interior (L×W×D) 21.48 x 16.42" x 12.54 (54.6 x 41.7 x 31.9 cm) Exterior (L×W×D) 24.76 x 19.57" x 13.90 (62.9 x 49.7 x 35.3 cm)

 Lid Depth
 2.01" (5.1 cm)

 Bottom Depth
 10.53" (26.7 cm)

 Total Depth
 12.54" (31.9 cm)

 Int Volume
 2.56 ft³ (0.072 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

MATERIALS

Body Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLORS

Black Desert Tan OD Green

WEIGHT

 Weight With Foam
 24.62 lbs (11.2 kg)

 Weight Empty
 21.20 lbs (9.6 kg)

 Buoyancy
 149.91 lbs (68 kg)

 Master Pack Weight
 26.90 lbs (12.2 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

CERTIFICATIONS

IP67 MIL C-4150J Def Stan 81-41

OTHER

Wheels 2
Extendable Handle yes
Master Pack 1
Nameplate yes
Military yes

ACCESSORIES



1609 Lid Organizer



1621 6 pc. Replacement Foam Set



1622Pick N Pluck™ Sections Only (set of 4)



1623 Replacement O-ring



1625 Padded Divider Set



1507 Quick Mounts - set of 4



1506TSA TSA Lock



1500D Desiccant Silica Gel



1610MP EZ-Click™ MOLLE Panel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 11-03-25