

# 1610M

# **Protector**

**Mobility Case** 

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican  $^{\text{\tiny TM}}$  Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- $\bullet$  4" diameter x 1.5" wide (10.2 x 3.8cm) heavy duty polyurethane wheels with stainless steel bearings
- · Water resistant, crushproof, and dust resistant
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors



#### **CONFIGURATIONS**



**1610M** Standard



1610MNF No Foam



**1610MWF** With Foam

#### **DIMENSIONS**

Interior (L×W×D) 21.78 x 16.69" x 10.62 (55.3 x 42.4 x 27 cm) Exterior (L×W×D) 26.20 x 23.00" x 13.68 (66.5 x 58.4 x 34.7 cm)

 Lid Depth
 2.05" (5.2 cm)

 Bottom Depth
 8.57" (21.8 cm)

 Total Depth
 10.62" (27 cm)

 Int Volume
 2.23 ft³ (0.063 m³)

 Padlock Hole Diameter
 5/16" (12.7 cm)

#### **MATERIALS**

**Body** Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

#### **COLORS**

Black

# WEIGHT

 Weight With Foam
 29.10 lbs (13.2 kg)

 Weight Empty
 26.30 lbs (11.9 kg)

# **TEMPERATURE**

**Minimum Temperature** -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

#### **CERTIFICATIONS**

IP57

# **OTHER**

Wheels2Extendable HandleyesMaster Pack1NameplateyesMilitaryyes

# **ACCESSORIES**



**1609** Lid Organizer



**1611** 5 pc. Replacement Foam Set



**1612**Pick N Pluck™ Sections Only (set of 3)



**1615** Padded Divider Set



**1623** Replacement O-ring



**1507** Quick Mounts - set of 4



**1506TSA** TSA Lock



**1500D** Desiccant Silica Gel



**1610MP** EZ-Click™ MOLLE Panel

# Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 08-23-25