

1610M

Protector

Mobility Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican $^{\text{\tiny TM}}$ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- \bullet 4" diameter x 1.5" wide (10.2 x 3.8cm) heavy duty polyurethane wheels with stainless steel bearings
- · Water resistant, crushproof, and dust resistant
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



1610M Standard



1610MNF No Foam



1610MWF With Foam

DIMENSIONS

Interior (L×W×D) 21.78 x 16.69" x 10.62 (55.3 x 42.4 x 27 cm) Exterior (L×W×D) 26.20 x 23.00" x 13.68 (66.5 x 58.4 x 34.7 cm)

 Lid Depth
 2.05" (5.2 cm)

 Bottom Depth
 8.57" (21.8 cm)

 Total Depth
 10.62" (27 cm)

 Int Volume
 2.23 ft³ (0.063 m³)

 Padlock Hole Diameter
 5/16" (12.7 cm)

MATERIALS

Body Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLORS

Black

WEIGHT

 Weight With Foam
 29.10 lbs (13.2 kg)

 Weight Empty
 26.30 lbs (11.9 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

CERTIFICATIONS

IP57

OTHER

Wheels2Extendable HandleyesMaster Pack1NameplateyesMilitaryyes

ACCESSORIES



1609 Lid Organizer



1611 5 pc. Replacement Foam Set



1612Pick N Pluck™ Sections Only (set of 3)



1615 Padded Divider Set



1623 Replacement O-ring



1507 Quick Mounts - set of 4



1506TSA TSA Lock



1500D Desiccant Silica Gel



1610MP EZ-Click™ MOLLE Panel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 10-16-25