



1780HL

Protector

Rifle Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **Fits M4, M16 firearms**
- **Watertight, crushproof, and dustproof**
- Detachable halves serve as mobile firearm racks
- Fast loading, lockable metal cross bar
- Humidity gauge changes color above 40%
- Lifetime Guarantee of Excellence
- Manual Pressure Equalization Valve
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Rigid polyethylene tray option for 12 firearms
- Made in the USA
- 4 heavy duty polyurethane wheels with stainless steel bearings for one-man mobility



DIMENSIONS

Interior (LxWxD)	41.12 x 21.54" x 14.88 (104.4 x 54.7 x 37.8 cm)
Exterior (LxWxD)	44.90 x 25.32" x 16.50 (114 x 64.3 x 41.9 cm)
Lid Depth	7.58" (19.3 cm)
Bottom Depth	7.30" (18.5 cm)
Total Depth	14.88" (37.8 cm)
Int Volume	7.63 ft³ (0.216 m³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Polypropylene
Latch	EXL
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane

COLORS

■ Black

WEIGHT

Weight With Foam	68.40 lbs (31 kg)
Weight Empty	53.00 lbs (24 kg)
Buoyancy	500.00 lbs (226.8 kg)
Master Pack Weight	77.00 lbs (34.9 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C)
Maximum Temperature 190°F (87.8 °C)

CERTIFICATIONS

Def Stan 81-41


OTHER

Wheels 4
Master Pack 1
Nameplate yes

ACCESSORIES



1781
6 pc. Replacement Foam Set



1782
Pick N Pluck™ Sections Only
(set of 4)



1783
Replacement O-ring



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Pelican
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 08-27-25