



## iM2075 Storm

The Pelican™ Storm Case™ has the same legendary DNA as our Pelican Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch. Guaranteed for life, the Pelican Storm case is made in the USA and engineered using the finest components.

- Guaranteed for life
- **Watertight, crushproof, and dustproof**
- Two Press & Pull Latches
- Two Padlockable Hasps
- Double-layered, Soft-grip Handle
- Vortex™ Valve
- Powerful Hinges
- Lightweight Strong HPX® Resin



### CONFIGURATIONS



**iM2075**  
Standard



**iM2075-X0000**  
No Foam



**iM2075-X0002**  
With Padded Dividers



**iM2075-X0001**  
With Foam

### DIMENSIONS

|                              |   |
|------------------------------|---|
| <b>Interior (LxWxD)</b>      | 9.50 x 7.50" x 7.25 (24.1 x 19.1 x 18.4 cm) |
| <b>Exterior (LxWxD)</b>      | 11.80 x 9.80" x 7.70 (30 x 24.9 x 19.6 cm)  |
| <b>Lid Depth</b>             | 1.50" (3.8 cm)                              |
| <b>Bottom Depth</b>          | 5.75" (14.6 cm)                             |
| <b>Total Depth</b>           | 7.25" (18.4 cm)                             |
| <b>Int Volume</b>            | 0.3 ft³ (0.008 m³)                          |
| <b>Padlock Hole Diameter</b> | 1/4" (6 mm)                                 |

### MATERIALS

|                         |  |
|-------------------------|--|
| <b>Body</b>             | Injection Molded HPX™ high performance resin |
| <b>Latch</b>            | Valox - Polybutylene Terephthalate (PBT)     |
| <b>Latch (Alt)</b>      | Xenoy - Polyester/Polycarbonate blend        |
| <b>O-Ring</b>           | EPDM   |
| <b>Pins</b>             | Stainless Steel                              |
| <b>Pins (Alt)</b>       | Aluminum                                     |
| <b>Foam</b>             | 1.3/1.35 polyester                           |
| <b>Purge Body</b>       | Valox - Polybutylene Terephthalate (PBT)     |
| <b>Purge Body (Alt)</b> | Xenoy - Polyester/Polycarbonate blend        |
| <b>Purge Vent</b>       | Gortex membrane                              |

## COLORS

■ Black

■ OD Green

■ Yellow

## WEIGHT

|                           |                    |
|---------------------------|--------------------|
| <b>Weight With Foam</b>   | 3.70 lbs (1.7 kg)  |
| <b>Weight Empty</b>       | 3.30 lbs (1.5 kg)  |
| <b>Buoyancy</b>           | 18.20 lbs (8.3 kg) |
| <b>Master Pack Weight</b> | 18.20 lbs (8.3 kg) |

## TEMPERATURE

|                            |                  |
|----------------------------|------------------|
| <b>Minimum Temperature</b> | -20°F (-28.9 °C) |
| <b>Maximum Temperature</b> | 140°F (60 °C)    |

## CERTIFICATIONS

**MIL-STD-810F**  
**ATA 300**  
**FED-STD-101C**

## FOAM PROPERTIES

|                       |                    |
|-----------------------|--------------------|
| <b>Layer 1 (Lid)</b>  | 1.12" Convolute    |
| <b>Layer 2 (Base)</b> | 0.63" Pad          |
| <b>Layer 3 (Base)</b> | 2.69" Pick N Pluck |
| <b>Layer 4 (Base)</b> | 2.69" Pick N Pluck |


## OTHER

|                    |     |
|--------------------|-----|
| <b>Master Pack</b> | 4   |
| <b>Military</b>    | yes |

## ACCESSORIES



**iM20XX-BEZEL**  
Base Bezel Kit



**iM2075-FOAM**  
4 pc. Replacement Foam Set



**iM2075-DIV**  
Padded Divider Set



**iM-VALVE-M-B**  
Manual Purge Valve



**iM-STRAP-S-VER2**  
Padded Shoulder Strap



**iM-LIDSTAY**  
Lid Stay



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 09-22-20*