

1300

Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

· Watertight, crushproof, and dustproof

- Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Stainless steel hardware



CONFIGURATIONS



1300 Standard



1300NF No Foam



1300WF With Foam

DIMENSIONS

 Interior (L×W×D)
 9.17 x 7.00" x 6.12 (23.3 x 17.8 x 15.5 cm)

 Exterior (L×W×D)
 10.62 x 9.68" x 6.87 (27 x 24.6 x 17.4 cm)

 Lid Depth
 1.18" (3 cm)

 Bottom Depth
 4.93" (12.5 cm)

 Total Depth
 6.11" (15.5 cm)

 Int Volume
 0.23 ft³ (0.007 m³)

MATERIALS

Body Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLORS

■ Black Orange Silver Yellow

WEIGHT

 Weight With Foam
 3.53 lbs (1.6 kg)

 Weight Empty
 3.09 lbs (1.4 kg)

 Buoyancy
 12.35 lbs (5.6 kg)

 Master Pack Weight
 16.85 lbs (7.6 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C)
Maximum Temperature 210°F (98.9 °C)

CERTIFICATIONS

IP67

Def Stan 81-41

OTHER

Master Pack 4 Military yes

ACCESSORIES

1507

Quick Mounts - set of 4

1506TSA

TSA Lock



Pelican

1500D

Desiccant Silica Gel

1500CI

Corrosion Intercept Kit