



1450 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **Watertight, crushproof, and dustproof**
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Easy open Double Throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



1450
Standard



1454
With Padded Dividers



1450NF
No Foam



1450WF
With Foam

DIMENSIONS

Interior (L×W×D)	14.66 x 10.24" x 6.12 (37.2 x 26 x 15.5 cm)
Exterior (L×W×D)	16.44 x 13.00" x 6.82 (41.8 x 33 x 17.3 cm)
Lid Depth	1.75" (4.4 cm)
Bottom Depth	4.37" (11.1 cm)
Total Depth	6.12" (15.5 cm)
Int Volume	0.53 ft ³ (0.015 m ³)
Padlock Hole Diameter	5/16" (8 mm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS


Purge Vent


3 Micron Hydrophobic Non-Woven

COLORS

 Black
 Silver

 Desert Tan
 Yellow

 Orange

 OD Green

WEIGHT

Weight With Foam 6.39 lbs (2.9 kg)
Weight Empty 5.51 lbs (2.5 kg)
Buoyancy 30.00 lbs (13.6 kg)
Master Pack Weight 33.35 lbs (15.1 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C)
Maximum Temperature 210°F (98.9 °C)

CERTIFICATIONS

IP67
MIL C-4150J
Def Stan 81-41
STANAG 4280

FOAM PROPERTIES

Layer 1 (Lid) 1.88" Convolute
Layer 2 (Base) 0.75" Pad
Layer 3 (Base) 3.50" Pick N Pluck

OTHER

Master Pack 4
Nameplate yes
Military yes

ACCESSORIES



1451
3 pc. Replacement Foam Set



1453
Replacement O-ring



1455
Padded Divider Set



1450PF
Special Application Panel
Frame



PL2
Padlock (2 pack)



1450TPKIT
TrekPak Case Divider Kit



1400TPDIV
Extra TrekPak Dividers



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 09-23-20