

# 1610 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican<sup>™</sup> Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Strong polyurethane wheels with stainless steel bearings
- Watertight, crushproof, and dustproof
- 3 level Pick N Pluck<sup>™</sup> with convoluted lid foam
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors



## CONFIGURATIONS



1610 Standard



1614 With Padded Dividers



**1610NF** No Foam



1610TP With TrekPak Divider System



1610WF With Foam

### DIMENSIONS

Interior (L×W×D) 21.78 x 16.69" x 10.62 (55.3 x 42.4 x 27 cm)   Exterior (L×W×D) 24.83 x 19.69" x 11.88 (63.1 x 50 x 30.2 cm)   Lid Depth 2.05" (5.2 cm)   Bottom Depth 8.57" (21.8 cm)   Total Depth 10.62" (27 cm)   Int Volume 2.23 ft <sup>3</sup> (0.063 m <sup>3</sup> )   Padlock Hole Diameter 0.31" (0.8 cm)		
Lid Depth 2.05" (5.2 cm)   Bottom Depth 8.57" (21.8 cm)   Total Depth 10.62" (27 cm)   Int Volume 2.23 ft <sup>3</sup> (0.063 m <sup>3</sup> )	Interior (L×W×D)	21.78 x 16.69" x 10.62 (55.3 x 42.4 x 27 cm)
Bottom Depth   8.57" (21.8 cm)     Total Depth   10.62" (27 cm)     Int Volume   2.23 ft <sup>3</sup> (0.063 m <sup>3</sup> )	Exterior (L×W×D)	24.83 x 19.69" x 11.88 (63.1 x 50 x 30.2 cm)
Total Depth   10.62" (27 cm)     Int Volume   2.23 ft <sup>3</sup> (0.063 m <sup>3</sup> )	Lid Depth	2.05" (5.2 cm)
<b>Int Volume</b> 2.23 ft <sup>3</sup> (0.063 m <sup>3</sup> )	Bottom Depth	8.57" (21.8 cm)
	Total Depth	10.62" (27 cm)
Padlock Hole Diameter 0.31" (0.8 cm)	Int Volume	2.23 ft <sup>3</sup> (0.063 m <sup>3</sup> )
	Padlock Hole Diameter	0.31" (0.8 cm)

#### MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

## COLORS

Black

Desert Tan

#### WEIGHT

Weight With Foam	22.30 lbs (10.1 kg)
Weight Empty	19.50 lbs (8.8 kg)
Buoyancy	119.93 lbs (54.4 kg)
Master Pack Weight	25.55 lbs (11.6 kg)

#### TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	190°F (87.8 °C)

#### CERTIFICATIONS

IP67	
Def Stan	81-41

#### OTHER

Wheels	2
Extendable Handle	yes
Master Pack	1
Nameplate	yes
Military	yes

## ACCESSORIES



**1609** Lid Organizer



1611 5 pc. Replacement Foam Set



**1612** Pick N Pluck<sup>™</sup> Sections Only (set of 3)



1615 Padded Divider Set



**1506TSA** TSA Lock



1623 Replacement O-ring



1500D Desiccant Silica Gel



**1610TPKIT** TrekPak Case Divider Kit



**1610TPDIV** Extra TrekPak Dividers



**1507** Quick Mounts - set of 4







**1610MP** EZ-Click™ MOLLE Panel **1500CI** Corrosion Intercept Kit

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com

Document created on 07-04-25