



## 3765PL

Right Angle Light

- Compact and Lightweight
- NFPA Compliant (National Fire Protection Agency) 1901
- Also Operates on 4 Standard AA Alkaline Batteries




### DIMENSIONS

|               |                 |
|---------------|-----------------|
| <b>Length</b> | 5.36" (13.6 cm) |
|---------------|-----------------|

### MATERIALS

|               |                                      |
|---------------|--------------------------------------|
| <b>Body</b>   | ABS                                  |
| <b>O-Ring</b> | Buna-N                               |
| <b>Lens</b>   | Polycarbonate (PC)                   |
| <b>Shroud</b> | Photo luminescent Polycarbonate (PC) |
| <b>Clip</b>   | Xenoy                                |

### COLORS

 High Visibility Yellow

### LIGHT SPECS

|                            |     |
|----------------------------|-----|
| <b>Lamp Type</b>           | LED |
| <b>Lamp Secondary Type</b> | LED |

### POWER

|                                |               |
|--------------------------------|---------------|
| <b>Battery Size</b>            | AA            |
| <b>Battery Type</b>            | NiMH          |
| <b>Battery Quantity</b>        | 4             |
| <b>Batteries Included</b>      | yes           |
| <b>Rechargeable</b>            | yes           |
| <b>Charge Time</b>             | 3 hrs 30 mins |
| <b>Battery Level Indicator</b> | 3 Blue LEDs   |
| <b>Volts</b>                   | 4.8v          |

### WEIGHT

|                              |                  |
|------------------------------|------------------|
| <b>Weight With Batteries</b> | 14.6 oz (414 gr) |
|------------------------------|------------------|

**Weight Without Batteries**

11.0 oz (312 gr)

**SWITCH**

**Switch Type**

Push Button

**Light Modes**

High / Low / Flashing

**CERTIFICATIONS**

**Class I, Division 1**

**Class I, Division 2**






**OTHER**

**Minimum Pack**

1

**Package Code**

B

| <b>FL1 STANDARD</b>   | <b>HIGH</b>   | <b>LOW</b>    | <b>DOWNCAST</b> | <b>FLASHING</b> |
|---|---------------|---------------|-----------------|-----------------|
|    | 237<br>LUMENS | 113<br>LUMENS | 32<br>LUMENS    | 140<br>LUMENS   |
|  | 3h 0mins      | 6h 30mins     | 14h 0mins       | 9h 0mins        |
|  | 301m          | 193m          | 28m             | 274m            |
|  | 22720cd       | 9354cd        | 192cd           | 18784cd         |
|  | IPX4          |               |                 |                 |

**ACCESSORIES**



**3769**  
Replacement Battery



**2467F**  
110V Transformer (USA)



**6061F**  
Direct Wiring Rig for Fast Charger



**8056F**  
12v Plug-in for Fast Charger

---

**Pelican**  
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 09-25-21*