



# 1930Z0

## L1™

Same features as L1™ 1930 LED with static-dissipation materials body. Being certified to ATEX safe for use in high-risk hazardous locations, Zone 0 (Category 1) areas, L1™ 1930Z0 LED is ideal for professionals who work in chemical, pharmaceutical, power, oil and gas, and fire rescue industries.



### DIMENSIONS

Length	2.64" (6.7 cm)
--------	----------------

### MATERIALS

Body	Anti-static Impact Modified PC/PBT
O-Ring	Ethylene Propylene
Lens	Polycarbonate (PC)
Shroud	Anti-static Impact Modified PC/PBT
Contact Spring Retainer	Phosphore Bronze

### COLOURS

 Gray
--

### LIGHT SPECS

Lamp Type	LED
-----------	-----

### POWER

Battery Size	LR 44
Battery Type	Alkaline
Battery Quantity	4
Batteries Included	yes
Volts	6.0v

### WEIGHT

Weight With Batteries	0.9 oz (26 gr)
Weight Without Batteries	0.6 oz (17 gr)
Packaged Weight	0.8 oz (23 gr)

### SWITCH

Switch Type	Push Button Tail
Light Modes	On / Off

CERTIFICATIONS

ATEX Zone 0

OTHER

Minimum Pack	12
Military	yes
Package Code	C

FL1 STANDARD	HIGH
	12 LUMENS
	4h 15mins
	17m
	70cd
	IPX4

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

Document created on 08-02-25