

9480

Remote Area Lighting Systems from Pelican are the complete lighting solution for first responders, industrial and aerospace applications.

- Built Pelican tough
- 3 pre-set light output levels
- Up to 4,000 lumens (calculated)
- Up to 28 hrs of run time
- Full time battery level indication with low level flashing indicator
- Deployable mast with 340 degree rotation
- Multiple deployment positions
- Convenient shoulder strap
- Quick release / Hot swappable battery design with 12 volt power supply



DIMENSIONS

Head (L×W×D) 8.25 x 5.75" x 2.25 (21 x 14.6 x 5.7 cm)
Closed (L×W×D) 15.50 x 6.50" x 10.25 (39.4 x 16.5 x 26 cm)

Light Head Height

(max)

23.75" (60.3 cm)

MATERIALS

Body Polypropylene
Head Aluminum
Mast Aluminum

Lens Polycarbonate (PC)

COLORS

Black Yellow

LIGHT SPECS

Lumens (High) 4000 Lumens (Med) 3000 1000 Lumens (Low) **Lamp Heads** 1 **Lamp Type** LED Number of LEDs 8 **Beam Spread** 125° **IP Rating** 54

POWER

 Run Time (High)
 6.00 hrs

 Run Time (Med)
 8.00 hrs

 Run Time (Low)
 28.00 hrs

Battery Type Sealed Lead Acid (SLA)

RechargeableyesBattery Lifespan500 cyclesCharge Time8 hrs

Battery Level Indicator Full-time battery level display and low battery warning (visible flashing)

Sockets (Primary) 1 Volts 12.0v

WEIGHT

Weight 27.50 lbs (12.5 kg)

SWITCH

Switch Type Silicone Rubber Keypad
Light Modes High / Medium / Low / Flashing

ACCESSORIES







9487 Padded Shoulder Strap



9489 Powerpack

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 07-02-25