

1465

Air

Pelican[™] Air cases are the first in a series of remarkable innovations engineered by Pelican, the pioneers of protective cases. For over 45 years Pelican has designed and crafted the most influential protective cases in the world, and we're just getting started.

With the launch of the Pelican™ Air line of cases, we're redefining the future of protection with a remarkable union of light and tough.

- Automatic pressure equalization valve balances interior pressure, keeps water out
- Fold down over-molded handle
- Stainless steel padlock protectors Press and Pull™ Latches
- · Limited Lifetime Warranty
- Super-light proprietary HPX^{2™} Polymer up to 40% lighter
- Waterproof O-ring seal
- User-customizable Pick N Pluck[™] foam
- Waterproof, crushproof, dustproof
- · Made in the USA



DIMENSIONS

Interior (L×W×D) 18.62 x 9.99" x 10.93 (47.3 x 25.4 x 27.8 cm) Exterior (L×W×D) 20.83 x 12.62" x 12.75 (52.9 x 32.1 x 32.4 cm)

Lid Depth 4.94" (12.5 cm) **Bottom Depth** 5.99" (15.2 cm) **Total Depth** 10.93" (27.8 cm) **Int Volume** 1.18 ft³ (0.033 m³) Padlock Hole Diameter 0.31" (0.8 cm)

MATERIALS

Proprietary Polypropylene Blend **Body**

Latch ABS **O-Ring EPDM**

Pins Stainless Steel Polyurethane **Foam**

Purge Body ABS

Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven **Purge Vent**

COLORS



WEIGHT

Weight With Foam 8.78 lbs (4 kg) **Weight Empty** 7.12 lbs (3.2 kg) **Buoyancy** 82.00 lbs (37.2 kg)

TEMPERATURE

Minimum Temperature 0°F (-17.8 °C) **Maximum Temperature** 140°F (60 °C)

ACCESSORIES



PL2 Padlock (2 pack)

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com

Document created on 10-17-25