



9455

Introducing the Pelican 9455 RALS, the world's first Class I Division 1, ATEX Zone 0 and IECEx ia safety certified remote area light. Now you can take remote area lighting to hazardous areas around the globe.

The 125° beam angle along with up to 1,600 lumens and providing up to 10 hours of run time, the 9455 will support full work shifts and deliver safe situational awareness. Weighing only 16 pounds and completely collapsible, makes for easy carry and quick set ups. The dual light modes, High/Low provide flexible options and is equipped with a 30 minute visible low battery warning indicator.

From confined spaces to tight manholes, nothing stops the Pelican 9455 RALS from illuminating the work site, safely.

****The repair of the 9455 needs to be conducted by a certified Pelican Products repair center due to the requirements of the safety certificate.**

- Class I Division 1, ATEX Zone 0, IECEx ia safety certified
- Up to 1,600 lumens
- Up to 10 hours run time
- NiMH rechargeable battery
- High / Low lighting modes
- Low battery indicator
- Hi Vis safety yellow
- Visit our 9455 explore page for more information



DIMENSIONS

| | |
|--------------------------------|--|
| Head (LxWxD) | 8.26 x 5.71" x 1.97 (21 x 14.5 x 5 cm) |
| Closed (LxWxD) | 15.35 x 7.87" x 9.06 (39 x 20 x 23 cm) |
| Light Head Height (max) | 31.50" (80 cm) |
| Cord Length | 12.60" (32 cm) |

MATERIALS

| | |
|-------------|--------------------------|
| Body | Polycarbonate (PC) / ABS |
| Head | Aluminum |
| Lens | Polycarbonate (PC) |

COLORS

| | |
|---|------------------------|
|  | High Visibility Yellow |
|---|------------------------|

LIGHT SPECS

| | |
|-----------------------|------|
| Lumens (High) | 1600 |
| Lumens (Low) | 800 |
| Lamp Type | LED |
| Number of LEDs | 10 |
| Beam Spread | 125° |
| IP Rating | 54 |

POWER

| | |
|------------------------|-----------|
| Run Time (High) | 5.00 hrs |
| Run Time (Low) | 10.00 hrs |

| | |
|--------------------------------|---------------------|
| Battery Type | NiMH |
| Battery Lifespan | 300 cycles |
| Charge Time | 8 hrs |
| Battery Level Indicator | Low battery warning |
| Watts | 21 W |
| Volts | 10.8v |

WEIGHT

| | |
|---------------|--------------------|
| Weight | 16.00 lbs (7.3 kg) |
|---------------|--------------------|

SWITCH

| | |
|--------------------|------------------------|
| Switch Type | Silicone Rubber Keypad |
| Light Modes | High / Low / Flashing |

CERTIFICATIONS

IECEX ia
Class I, Division 1
ATEX Zone 0
InMetro

ACCESSORIES



1460AALG
1460 Case with custom fit foam

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 09-02-25