



3415M

Right Angle Light

The most versatile intrinsically safe work light in the world, with magnet clip.

The 3415M (magnet version) is the ultimate safety certified compact work light. The Class I II III Division 1 certifications provide the security needed for most hazardous locations. The 3410M is equipped with both a spot and flood LED for close-up as well as distance, so you can have wide area light in the immediate work area and still penetrate darkness hundreds of yards away. It can be activated to run one or both LEDs with 3 levels of brightness. The articulating head and built-in clip allows the light to be directed wherever it is needed, while a heavy duty magnet allows the light to be snapped to steel surfaces. The full time battery level indicator ensures you will always know where your battery status is.

The Pelican 3415M- a professional grade multi-task lighting tool that will help you get the job done- under any circumstances.

- Articulating Light Head
- Full Time Battery Level Indication
- Class I, Class II, Class III - Division 1 Safety Certified
- Attached clip with integrated magnet
- Security Lanyard
- Split ring installed
- 2 modes: spot, flashing




DIMENSIONS

Length	7.44" (18.9 cm)
--------	-----------------

MATERIALS

Body	ABS
O-Ring	NBR
Lens	Polycarbonate (PC)
Shroud	ABS
Clip	ABS
Contact Spring Retainer	Stainless Steel / Phosphore Bronze / Brass Nickel Plate

COLORS

 High Visibility Yellow
--

LIGHT SPECS

Lamp Type	LED
Lamp Secondary Type	LED

POWER

Battery Size	AA
Battery Type	Alkaline
Battery Quantity	3
Volts	4.5v

WEIGHT






Weight With Batteries	9.6 oz (272 gr)
Weight Without Batteries	7.1 oz (201 gr)

SWITCH

Switch Type	Push Button
Light Modes	High / Flashing

CERTIFICATIONS

Class I, Division 1
Class II, Division 1
Class III, Division 1
IECEX ia

FL1 STANDARD	SPOT / FLOOD	FLOOD	SPOT
	336 LUMENS	177 LUMENS	186 LUMENS
	6h 0mins	15h 0mins	14h 0mins
	133m	37m	135m
	4418cd	336cd	4544cd
	IPX8 (1m)		