

0370

Protector

Cube Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Large 2-person fold down handles
- Watertight, crushproof, and dustproof
- 3 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors



DIMENSIONS

Interior (L×W×D) 24.00 x 24.00 " x 24.00 (61 x 61 x 61 cm) Exterior (L×W×D) 26.50 x 26.50 " x 25.25 (67.3 x 67.3 x 64.1 cm)

 Lid Depth
 5.00" (12.7 cm)

 Bottom Depth
 19.00" (48.3 cm)

 Total Depth
 24" (61 cm)

 Int Volume
 8 ft³ (0.227 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

MATERIALS

Body Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLORS



WEIGHT

 Weight With Foam
 41.00 lbs (18.6 kg)

 Weight Empty
 31.97 lbs (14.5 kg)

 Buoyancy
 465.18 lbs (211 kg)

 Master Pack Weight
 46.78 lbs (21.2 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

CERTIFICATIONS

IP67

Def Stan 81-41

OTHER

Master Pack1NameplateyesReduced AreayesMilitaryyes

ACCESSORIES











0357 Cube Case Mobility Package

0371 8 pc. Replacement Foam Set

0373 Replacement O-ring

0375 Padded Divider Set

0379 Lid Organizer







1506TSA TSA Lock



1500D Desiccant Silica Gel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com

Document created on 08-30-25