

0500 Protector

Transport Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican[™] Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Can be inverted and used as a pallet with an airtight cover
- Fit two 0500 Cases per pallet, four when stacked!
- Watertight, crushproof, and dustproof
- Double wide grip fold down handles makes lifting easy
- Dual Integrated Automatic Pressure Equalization Valves
- Easy open double-throw latches
- Lid is completely removable
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Optional Caster Wheel Kit complete with brakes
- Optional Pallet Riser Kit
- · Store documents outside the case with our Document Container



DIMENSIONS

Interior (L×W×D)	34.95 x 18.45" x 25.25 (88.8 x 46.9 x 64.1 cm)
Exterior (L×W×D)	39.95 x 23.45" x 28.65 (101.5 x 59.6 x 72.8 cm)
Lid Depth	2.25" (5.7 cm)
Bottom Depth	23.00" (58.4 cm)
Total Depth	25.25" (64.1 cm)
Int Volume	9.42 ft³ (0.267 m³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Polypropylene
Latch	EXL
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLORS

Black

WEIGHT

Weight With Foam	58.60 lbs (26.6 kg)
Weight Empty	50.00 lbs (22.7 kg)
Buoyancy	780.00 lbs (353.8 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	190°F (87.8 °C)

1

OTHER

Master Pack

ACCESSORIES



 Pelican

 23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

 sales@pelican.com

 • www.pelican.com

Document created on 09-02-25