

# 250QT

## Elite

Pelican Products, Inc. is proud to announce our bear resistant certification from the Interagency Grizzly Bear Committee.

The purpose of this certification is to help keep bears safe and significantly reduce bear-human encounters by ensuring that bears do not have access and become conditioned to anthropogenic foods and other bear attractants that increase these encounters.

This certification involves intense impact and penetration testing by use of visual inspection, mechanical methods and captive Grizzly Bear testing over extended periods of time.

\*\*Pelican™ Elite Coolers are certified bear-resistant by the IGBC under certification numbers 3365, 3366, 3373, 3374, 3375, 3376

- Dual Handle System (Molded-in & Hinged Handles)
- Extreme ice retention, freezer grade gasket, 2" polyurethane insulation
- Press & Pull Latches (Wide for Gloved Use)
- Molded-In Tie Downs
- Non-Skid & Non-Marking Raised Feet
- Molded-In Lock Hasp, Stainless Steel Plate
- Sloped Drain & Tethered Threaded Plug (Garden Hose Attachable)
- Corrosion Resistant Stainless Steel Hardware
- Integrated Fish Scale on Lid
- Made in USA
- · Guaranteed for life
- Custom Color Program



## **DIMENSIONS**

 Interior (L×W×D)
 50.25 x 17.00" x 17.50 (127.6 x 43.2 x 44.5 cm)

 Exterior (L×W×D)
 61.13 x 27.50" x 27.50 (155.3 x 69.9 x 69.9 cm)

 Volume
 250.00QT (236.59 L)

 Int Volume
 8.65 ft³ (0.245 m³)

 Insulation Thickness
 2.00" (5.1 cm)

## **MATERIALS**

**Body** Polyethylene

Latch ABS Handle TPE

SpigotPolypropyleneHardwareStainless SteelInsulationPolyurethane

#### **COLORS**

White

#### WEIGHT

**Weight** 92.00 lbs (41.7 kg)

#### IGBC Certified Bear Resistant

## **ACCESSORIES**







**TDKIT** Tie Down Kit



**PI-5LB** 5lb Ice Pack



PL2 Padlock (2 pack)



**CL1** Cable Lock



Cable Lock (2 pack)



**PI-1LB** 1lb Ice Pack

#### Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 09-16-25