



V800

Vault

Double Rifle Case

Built for hard use, high impact and supreme weather resistance, new Vault series gun cases are the most rugged and secure in their class. Equipped with a host of premium protective features at a price more hunters and shooters can afford, as only the 42-year veteran of hard knocks could deliver.

- Four layers of protective foam
- Crushproof, dustproof, and weather resistant
- High-impact polymer assures protection of your firearm, via road, trail or air
- Heavy duty handles are ergonomic and will stand up in even the toughest conditions
- Six push button latches offer secure closure with easy-open access
- Carry two scoped rifles with absolute confidence



DIMENSIONS

| | |
|------------------------------|--|
| Interior (LxWxD) | 53.00 x 16.00" x 6.00 (134.6 x 40.6 x 15.2 cm) |
| Exterior (LxWxD) | 56.11 x 19.15" x 6.65 (142.5 x 48.6 x 16.9 cm) |
| Lid Depth | 1.57" (4 cm) |
| Bottom Depth | 4.43" (11.3 cm) |
| Total Depth | 6" (15.2 cm) |
| Int Volume | 2.94 ft ³ (0.083 m ³) |
| Padlock Hole Diameter | 5/16" (8 mm) |

MATERIALS

| | |
|-------------------|--------------------------------|
| Body | Polyethylene |
| Latch | ABS |
| O-Ring | Polymer |
| Pins | Stainless Steel |
| Foam | 1.3 lb Polyurethane |
| Purge Body | ABS |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

COLORS

| | |
|---|---|
|  Black |  Tan |
|---|---|

WEIGHT

| | |
|---------------------------|---------------------|
| Weight With Foam | 24.95 lbs (11.3 kg) |
| Weight Empty | 19.60 lbs (8.9 kg) |
| Master Pack Weight | 28.76 lbs (13 kg) |

TEMPERATURE

| | |
|----------------------------|----------------|
| Minimum Temperature | 0°F (-17.8 °C) |
| Maximum Temperature | 140°F (60 °C) |

OTHER

Wheels

2


ACCESSORIES



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



V800FS
4 pc. Replacement Foam Set

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 07-02-22