

# 1465EMS

#### Air

**EMS** Case

When every second counts, you can depend on the new Pelican<sup> $\mathrm{TM}$ </sup>; Air 1465EMS case to keep you moving through the harshest terrain. Weighing in at only 13.2 pounds (empty) and crushproof, the Pelican<sup> $\mathrm{TM}$ </sup> Air 1465EMS case minimizes strain while protecting vital medical supplies without weighing you down.

- Automatic pressure equalization valve balances interior pressure, keeps water out
- Fold down over-molded handle
- · Stainless steel padlock protectors
- Removable trays are easy to wipe down to keep sanitized
- Three tier customizable pullout trays give you the flexibility to organize
- Storage bracket keeps used and sharp objects contained
- Press & Pull latches have been tested for extreme pressure and impact situations
- Limited Lifetime Warranty
- Super-light proprietary HPX<sup>2™</sup> Polymer up to 40% lighter
- Waterproof O-ring seal
- \*Sharps container not included
- Waterproof, crushproof, dustproof
- · Made in the USA



#### **DIMENSIONS**

Interior (L×W×D) 18.62 x 9.99" x 10.93 (47.3 x 25.4 x 27.8 cm) Exterior (L×W×D) 20.83 x 12.62" x 12.75 (52.9 x 32.1 x 32.4 cm)

 Lid Depth
 4.94" (12.5 cm)

 Bottom Depth
 5.99" (15.2 cm)

 Total Depth
 10.93" (27.8 cm)

 Int Volume
 1.18 ft³ (0.033 m³)

 Padlock Hole Diameter
 5/16" (12.7 cm)

#### **MATERIALS**

**Body** Proprietary Polypropylene Blend

Latch ABS O-Ring EPDM

Pins Stainless Steel

Purge Body ABS

Purge Vent Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

Tray ABS

#### **COLORS**

Orange

## WEIGHT

**Weight** 13.30 lbs (6 kg)

### **TEMPERATURE**

 $\begin{array}{ll} \mbox{Minimum Temperature} & -60\,^{\circ}\mbox{F} \; (-51.1\,^{\circ}\mbox{C}) \\ \mbox{Maximum Temperature} & 160\,^{\circ}\mbox{F} \; (71.1\,^{\circ}\mbox{C}) \\ \end{array}$ 

### **ACCESSORIES**



**PL2** Padlock (2 pack)

#### Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com

Document created on 04-25-24