



1170 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **The hand-held electronics protection solution**
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Stainless steel hardware



DIMENSIONS

Interior (LxWxD)	10.54 x 6.04" x 3.16 (26.8 x 15.3 x 8 cm)
Exterior (LxWxD)	11.64 x 8.34" x 3.78 (29.6 x 21.2 x 9.6 cm)
Lid Depth	1.08" (2.7 cm)
Bottom Depth	2.08" (5.3 cm)
Total Depth	3.16" (8 cm)
Int Volume	0.12 ft³ (0.003 m³)
Padlock Hole Diameter	0.19" (0.5 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLORS

 Black	 Desert Tan	 Orange	 OD Green
 Silver	 Yellow		

WEIGHT

Weight With Foam	2.10 lbs (1 kg)
Weight Empty	1.96 lbs (0.9 kg)
Buoyancy	7.25 lbs (3.3 kg)
Master Pack Weight	12.79 lbs (5.8 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C)
Maximum Temperature 210°F (98.9 °C)

CERTIFICATIONS

IP67

OTHER

Master Pack 6

ACCESSORIES



1171
3 pc. Replacement Foam Set



1173
Replacement O-ring



1507
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Pelican
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 04-19-24