

# 1750

## **Protector**

Long Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Strong polyurethane wheels with stainless steel bearings
- · Watertight, crushproof, and dustproof
- 3-piece foam set
- Automatic pressure equalization valve balances interior pressure, keeps water out
- · Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors
- 12 lid bosses for mounting of multiple 1500MP EZ-Click™ MOLLE Panels
- Fold-down side handles on both ends additional carrying options
- New fold-down over-molded top and side handles
- • \*1500 EZ-Click MOLLE Panels sold separately. Now available for purchase



### **DIMENSIONS**

Interior (L×W×D) 50.38 x 13.33" x 5.33 (128 x 33.9 x 13.5 cm) Exterior (L×W×D) 53.60 x 16.05" x 6.13 (136.1 x 40.8 x 15.6 cm)

 Int Volume
 2.07 ft³ (0.059 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

### **MATERIALS**

**Body** Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

#### **COLORS**

Black

#### WEIGHT

Weight With Foam 26.70 lbs (12.1 kg)
Weight Empty 21.00 lbs (9.5 kg)

#### **TEMPERATURE**

Minimum Temperature -40°F (-40 °C)

# OTHER

Nameplate

yes

# **ACCESSORIES**



**1500MP** EZ-Click™ MOLLE Panel



**1506TSA** TSA Lock



**1500D** Desiccant Silica Gel



1753 Replacement O-ring

### Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com

Document created on 07-05-25