



0370

Protector

Cube Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **Large 2-person fold down handles**
- **Watertight, crushproof, and dustproof**
- 3 level Pick N Pluck™ with convoluted lid foam
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel hardware and padlock protectors



DIMENSIONS

Interior (LxWxD)	24.00 x 24.00" x 24.00 (61 x 61 x 61 cm)
Exterior (LxWxD)	26.50 x 26.50" x 25.25 (67.3 x 67.3 x 64.1 cm)
Lid Depth	5.00" (12.7 cm)
Bottom Depth	19.00" (48.3 cm)
Total Depth	24" (61 cm)
Int Volume	8 ft ³ (0.227 m ³)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLORS

■ Black

WEIGHT

Weight With Foam	41.00 lbs (18.6 kg)
Weight Empty	31.97 lbs (14.5 kg)
Buoyancy	465.18 lbs (211 kg)
Master Pack Weight	46.78 lbs (21.2 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C)
Maximum Temperature 210°F (98.9 °C)

CERTIFICATIONS

IP67
Def Stan 81-41
STANAG 4280

OTHER

Master Pack 1
Nameplate yes
Reduced Area yes
Military yes

ACCESSORIES



0357
Cube Case Mobility Package



0371
8 pc. Replacement Foam Set



0373
Replacement O-ring



0375
Padded Divider Set



0379
Lid Organizer



1507
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 11-26-21