



1650 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **4 strong polyurethane wheels with stainless steel bearings**
- **Watertight, crushproof, and dustproof**
- 2 level Pick N Pluck™ with convoluted lid foam
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Easy open Double Throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Retractable extension handle
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



1650
Standard



1654
With Padded Dividers



1650NF
No Foam



1650TP
With TrekPak Divider System



1650WF
With Foam

DIMENSIONS

| | |
|------------------------------|--|
| Interior (LxWxD) | 28.57 x 17.52" x 10.65 (72.6 x 44.5 x 27.1 cm) |
| Exterior (LxWxD) | 31.59 x 20.47" x 12.45 (80.2 x 52 x 31.6 cm) |
| Lid Depth | 1.81" (4.6 cm) |
| Bottom Depth | 8.84" (22.5 cm) |
| Total Depth | 10.65" (27.1 cm) |
| Int Volume | 3.08 ft ³ (0.087 m ³) |
| Padlock Hole Diameter | 5/16" (8 mm) |

MATERIALS

| | |
|-------------------|--------------------------------|
| Body | Polypropylene |
| Latch | ABS |
| O-Ring | Polymer |
| Pins | Stainless Steel |
| Foam | 1.3 lb Polyurethane |
| Purge Body | ABS |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

COLORS

■ Black

■ Desert Tan

■ OD Green

WEIGHT

| | |
|---------------------------|----------------------|
| Weight With Foam | 28.06 lbs (12.7 kg) |
| Weight Empty | 24.03 lbs (10.9 kg) |
| Buoyancy | 181.00 lbs (82.1 kg) |
| Master Pack Weight | 30.10 lbs (13.7 kg) |

TEMPERATURE

| | |
|----------------------------|-----------------|
| Minimum Temperature | -40°F (-40 °C) |
| Maximum Temperature | 210°F (98.9 °C) |

CERTIFICATIONS

IP67
MIL C-4150J
Def Stan 81-41
STANAG 4280
ATA 300

OTHER

| | |
|--------------------------|-----|
| Wheels | 4 |
| Extendable Handle | yes |
| Master Pack | 1 |
| Nameplate | yes |
| Reduced Area | yes |
| Military | yes |

ACCESSORIES



1651
4 pc. Replacement Foam Set



1652
Pick N Pluck™ Sections Only
(set of 2)



1653
Replacement O-ring



1655
Padded Divider Set



1659
Photo/Lid Organizer



1650TPKIT
TrekPak Case Divider Kit



1650TPDIV
Extra TrekPak Dividers



1507
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



1650MP
EZ-Click™ MOLLE Panel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 06-24-22