



1510SC

Protector

Studio Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **2 in 1 protection: detachable computer sleeve and accessories pouch**
- Maximum airline carry on size*
- **Strong polyurethane wheels with stainless steel bearings**
- **Watertight, crushproof, and dustproof**
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded top and side handles
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Fits notebook computers up to 14.4" x 11.1" x 1.7" (36.58 x 28.19 x 4.32 cm)
- * Check with your airline for exact measurement requirements.



DIMENSIONS

| | |
|------------------------------|-----------------------------------------------|
| Interior (LxWxD) | 19.75 x 11.00" x 7.60 (50.2 x 27.9 x 19.3 cm) |
| Exterior (LxWxD) | 22.00 x 13.81" x 9.00 (55.9 x 35.1 x 22.9 cm) |
| Lid Depth | 1.79" (4.5 cm) |
| Bottom Depth | 5.79" (14.7 cm) |
| Total Depth | 7.58" (19.3 cm) |
| Int Volume | 0.96 ft ³ (0.027 m ³) |
| Padlock Hole Diameter | 5/16" (8 mm) |

MATERIALS

| | |
|-------------------|--------------------------------|
| Body | Polypropylene |
| Latch | ABS |
| O-Ring | Polymer |
| Pins | Stainless Steel |
| Foam | 1.3 lb Polyurethane |
| Purge Body | ABS |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

COLORS

■ Black

WEIGHT

Weight With Foam 13.60 lbs (6.2 kg)

| | |
|---------------------------|---------------------|
| Weight Empty | 11.99 lbs (5.4 kg) |
| Buoyancy | 64.15 lbs (29.1 kg) |
| Master Pack Weight | 32.43 lbs (14.7 kg) |

TEMPERATURE

| | |
|----------------------------|-----------------|
| Minimum Temperature | -40°F (-40 °C) |
| Maximum Temperature | 210°F (98.9 °C) |

CERTIFICATIONS

IP67
Def Stan 81-41
STANAG 4280

OTHER

| | |
|--------------------------|-----|
| Wheels | 2 |
| Extendable Handle | yes |
| Master Pack | 2 |
| Nameplate | yes |
| Reduced Area | yes |
| Military | yes |

ACCESSORIES



1513
Replacement O-ring



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



1500CI
Corrosion Intercept Kit

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 08-15-22