

1670

Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- 4 strong polyurethane wheels with stainless steel bearings
- · Watertight, crushproof, and dustproof
- 2 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors
- Two oversized fold down handles for extra grip



DIMENSIONS

Interior (L×W×D) 28.10 x 16.49" x 9.19 (71.4 x 41.9 x 23.3 cm) Exterior (L×W×D) 31.04 x 19.39" x 11.17 (78.8 x 49.3 x 28.4 cm)

 Lid Depth
 1.80" (4.6 cm)

 Bottom Depth
 7.39" (18.8 cm)

 Total Depth
 9.19" (23.3 cm)

 Int Volume
 2.46 ft³ (0.07 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

MATERIALS

Body Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLORS



WEIGHT

 Weight With Foam
 26.00 lbs (11.8 kg)

 Weight Empty
 23.00 lbs (10.4 kg)

 Buoyancy
 182.00 lbs (82.6 kg)

 Master Pack Weight
 49.00 lbs (22.2 kg)


TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

OTHER

Wheels 4 Master Pack 1

ACCESSORIES







1675 Padded Divider Set



1507 Quick Mounts - set of 4



1506TSA TSA Lock



1500D Desiccant Silica Gel



PL2 Padlock (2 pack)

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com

Document created on 04-26-24