



3765PL

Right Angle Light

- Compact and Lightweight
- NFPA Compliant (National Fire Protection Agency) 1901
- Also Operates on 4 Standard AA Alkaline Batteries




DIMENSIONS

Length	5.36" (13.6 cm)
---------------	-----------------

MATERIALS

Body	ABS
O-Ring	Buna-N
Lens	Polycarbonate (PC)
Shroud	Photo luminescent Polycarbonate (PC)
Clip	Xenoy

COLORS

 High Visibility Yellow

LIGHT SPECS

Lamp Type	LED
Lamp Secondary Type	LED

POWER

Battery Size	AA
Battery Type	NiMH
Battery Quantity	4
Batteries Included	yes
Rechargeable	yes
Charge Time	3 hrs 30 mins
Battery Level Indicator	3 Blue LEDs
Volts	4.8v

WEIGHT

Weight With Batteries	14.6 oz (414 gr)
------------------------------	------------------

Weight Without Batteries

11.0 oz (312 gr)

SWITCH

Switch Type

Push Button

Light Modes

High / Low / Flashing

CERTIFICATIONS

Class I, Division 1

Class I, Division 2






OTHER

Minimum Pack

1

Package Code

B

FL1 STANDARD	HIGH	LOW	DOWNCAST	FLASHING
	237 LUMENS	113 LUMENS	32 LUMENS	140 LUMENS
	3h 0mins	6h 30mins	14h 0mins	9h 0mins
	301m	193m	28m	274m
	22720cd	9354cd	192cd	18784cd
	IPX4			

ACCESSORIES



3769
Replacement Battery



2467F
110V Transformer (USA)



6061F
Direct Wiring Rig for Fast Charger



8056F
12v Plug-in for Fast Charger

Pelican
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 06-30-22