



iM2200 Storm

The Pelican™ Storm Case™ has the same legendary DNA as our Pelican Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch. Guaranteed for life, the Pelican Storm case is made in the USA and engineered using the finest components.

- Guaranteed for life
- **Watertight, crushproof, and dustproof**
- Two Press & Pull Latches
- Two Padlockable Hasps
- Double-layered, Soft-grip Handle
- Vortex™ Valve
- Powerful Hinges
- Lightweight Strong HPX® Resin



CONFIGURATIONS



iM2200
Standard



iM2200-X0000
No Foam



iM2200-X0002
With Padded Dividers



iM2200-X0001
With Foam

DIMENSIONS

Interior (LxWxD)	15.00 x 10.50" x 6.00 (38.1 x 26.7 x 15.2 cm)
Exterior (LxWxD)	16.20 x 12.70" x 6.60 (41.1 x 32.3 x 16.8 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	4.00" (10.2 cm)
Total Depth	6" (15.2 cm)
Int Volume	0.55 ft ³ (0.016 m ³)
Padlock Hole Diameter	0.28" (0.7 cm)

MATERIALS

Body	Injection Molded HPX™ high performance resin
Latch	Valox - Polybutylene Terephthalate (PBT)
Latch (Alt)	Xenoy - Polyester/Polycarbonate blend
O-Ring	EPDM
Pins	Stainless Steel
Pins (Alt)	Aluminum
Foam	1.3/1.35 polyester
Purge Body	Valox - Polybutylene Terephthalate (PBT)
Purge Body (Alt)	Xenoy - Polyester/Polycarbonate blend
Purge Vent	Gortex membrane

COLOURS

■ Black

■ Yellow

WEIGHT

Weight With Foam	6.10 lbs (2.8 kg)
Weight Empty	4.90 lbs (2.2 kg)
Buoyancy	35.50 lbs (16.1 kg)
Master Pack Weight	28.60 lbs (13 kg)

TEMPERATURE

Minimum Temperature	-20°F (-28.9 °C)
Maximum Temperature	140°F (60 °C)

CERTIFICATIONS

IP67

OTHER

Master Pack	4
Military	yes

ACCESSORIES



iM2200-FOAM
4 pc. Replacement Foam Set



iM2200-BEZEL-LID
Lid Bezel Kit



iM2200-BEZEL
Base Bezel Kit



iM-STRAP-S-VER2
Padded Shoulder Strap



iM-LIDSTAY
Lid Stay




iM2200TPKIT
TrekPak Case Divider Kit



1400TPDIV
Extra TrekPak Dividers



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 09-19-24