



## iM2975

### Storm

Travel Case

The Pelican™ Storm Case™ has the same legendary DNA as our Pelican Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch.

Guaranteed for life, the Pelican Storm case is made in the USA and engineered using the finest components.

- Five Press & Pull Latches
- Guaranteed For Life
- Two Padlockable Hasps
- Two Double-layered, Soft-grip Handles
- Two Integrated Key Lockable Latches
- Powerful Hinges
- O-ring seal
- Two stainless steel padlock protectors
- Specialized molded foam interior designed for Pump or Semi-automatic shotguns and accessories
- Retention Strap Instructions




## CONFIGURATIONS



**iM2975**  
Standard



**iM2975-X0000**  
No Foam



**iM2975-X0002**  
With Padded Dividers



**iM2975-X0001**  
With Foam

## DIMENSIONS

<b>Interior (L x W x D)</b>	29.00 x 18.00" x 13.80 (73.7 x 45.7 x 35.1 cm)
<b>Exterior (L x W x D)</b>	31.30 x 20.40" x 15.50 (79.5 x 51.8 x 39.4 cm)
<b>Lid Depth</b>	2.00" (5.1 cm)
<b>Bottom Depth</b>	11.80" (30 cm)
<b>Total Depth</b>	13.8" (35.1 cm)
<b>Int Volume</b>	4.17 ft <sup>3</sup> (0.118 m <sup>3</sup> )

## MATERIALS

<b>Body</b>	Injection Molded HPX™ high performance resin
<b>Latch</b>	Valox - Polybutylene Terephthalate (PBT)
<b>Latch (Alt)</b>	Xenoy - Polyester/Polycarbonate blend
<b>O-Ring</b>	EPDM
<b>Pins</b>	Stainless Steel
<b>Pins (Alt)</b>	Aluminum
<b>Foam</b>	1.3/1.35 polyester
<b>Purge Body</b>	Valox - Polybutylene Terephthalate (PBT)

## Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

**Purge Body (Alt)**

Xenoy - Polyester Polycarbonate • [sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

**Purge Vent**

Gortex membrane

Document created on 04-22-19

# COLOURS

■ Black

■ OD Green

# WEIGHT

<b>Weight With Foam</b>	29.50 lbs (13.4 kg)
<b>Weight Empty</b>	22.80 lbs (10.3 kg)
<b>Buoyancy</b>	250.02 lbs (113.4 kg)
<b>Master Pack Weight</b>	31.50 lbs (14.3 kg)

# TEMPERATURE

<b>Minimum Temperature</b>	-20°F (-28.9 °C)
<b>Maximum Temperature</b>	140°F (60 °C)

# CERTIFICATIONS

MIL-STD-810F  
ATA 300  
FED-STD-101C

# FOAM PROPERTIES

<b>Layer 1 (Lid)</b>	2.00" Convolute
<b>Layer 2 (Base)</b>	0.63" Pad
<b>Layer 3 (Base)</b>	1.88" Pick N Pluck
<b>Layer 4 (Base)</b>	1.88" Pick N Pluck
<b>Layer 5 (Base)</b>	1.88" Pick N Pluck
<b>Layer 6 (Base)</b>	1.88" Pick N Pluck
<b>Layer 7 (Base)</b>	1.88" Pick N Pluck
<b>Layer 8 (Base)</b>	1.88" Pick N Pluck

# OTHER

<b>Extendable Handle</b>	yes
<b>Master Pack</b>	1
<b>Military</b>	yes

# ACCESSORIES